



CANON SOLUTIONS AMERICA

imageRUNNER
ADVANCE

715iF / 715iFZ
615iF / 615iFZ
525iF / 525iFZ 

imageRUNNER ADVANCE 715iF II Series

Black-and-White | Compact | Multifunction

Print up to 75 ppm (BW)

Scan up to 100 ipm (300 dpi) (BW, color, duplex)

Print up to 8-1/2" x 14"

3,200-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology; better **control** sensitive information and print-related costs; and help ensure that technology investments proactively **evolve** with changing needs.



WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences with My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive™ and Box.¹
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.



SECURITY

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control who has access to the device, and to which features, using a host of flexible authentication methods – picture login, PIN code, user name/password, or card access.²



COST MANAGEMENT

- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- uniFLOW Online Express, a standard cloud-based solution, provides a centralized dashboard with up-to-the-minute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



QUALITY AND RELIABILITY

- The All-In-One cartridge is designed for long life and easy replacement, helping to decrease the need for service intervention and increase uptime.
- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Designed to achieve maximum uptime with status notifications to help keep supplies replenished and intuitive maintenance videos for consumables replacement.



SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally-conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR® certified and rated EPEAT® Gold.³

Standard Model (715iF II/615iF II/525iF II)*



Finisher Model (715iFZ II/615iFZ II/525iFZ II)



CASSETTE FEEDING UNIT-ARI

- 550-sheet capacity and cabinet for storage
- Supports up to Legal
- Supports 60 to 135 g/m²



HIGH CAPACITY CASSETTE FEEDING UNIT-DI

- 2,550-sheet capacity (550-sheet upper cassette, 2,000-sheet lower cassette)
- Supports up to Legal
- Supports 60 to 135 g/m²



CASSETTE MODULE-AGI**

- 550-sheet capacity
- Supports up to Legal
- Supports 60 to 135 g/m²

ENVELOPE CASSETTE MODULE-AI▲

- 75-sheets (Envelope)
- Supports COM10 (No.10), Monarch, DL, ISO-C5
- Supports 80 to 100 g/m²



CABINET TYPE-U▲▲

- Provides base (with wheels) for cassettes

* Finisher cannot be added after purchase.

** Can add up to three additional cassettes. When a combined total of three Cassette Module-AGI/Envelope Cassette Module-AI units are added to a finisher model, Cabinet Type-U is required.

▲ Maximum of two Envelope Cassette Module-AI units can be configured and only as the first or second additional cassette.

▲▲ Cabinet Type-U is required when three additional cassettes are added to a finisher model.

SPECIFICATIONS

Main Unit

Type

Monochrome Laser Multifunction

Core Functions

Print, Copy, Scan, Send, Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

10.1" WSVGA Color Touch-panel

Memory

3.0 GB RAM

Hard Disk Drive

250 GB

Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T,

Wireless LAN (IEEE 802.11 b/g/n)

Optional:

NFC, Bluetooth

Others

Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),

USB 2.0 x1 (Device)

Optional:

Copy Control Interface

Paper Capacity (LTR, 20 lb. Bond)

Standard: 650 Sheets

Maximum: 3,200 Sheets

Paper Sources (LTR, 20 lb. Bond)

Standard: 550-sheet Paper Cassette, 100-sheet Stack Bypass

Optional: 550-sheet (CASSETTE FEEDING UNIT-ARI), 2,550-sheet (HIGH CAPACITY CASSETTE FEEDING UNIT-DI), 550-sheet (CASSETTE MODULE-AGI), 75-envelope (ENVELOPE CASSETTE MODULE-AI)

Paper Output Capacity (LTR, 20 lb. Bond)

Standard Model: 500 Sheets

Finisher Model: 1,000 Sheets (Base tray: 500 Sheets, Upper tray: 400 Sheets, Lower tray: 100 Sheets)

Finishing Capabilities

Standard Model: Collate, Group

Finisher Model: Collate, Group, Offset, Staple

Supported Media Types

Cassettes: Thin, Plain, Recycled, Color, Heavy, Labels, Bond, Pre-punched

Stack Bypass: Thin, Plain, Recycled, Color, Heavy, Transparency, Bond, Envelope

Supported Media Sizes

Cassette (Std.): Letter, Executive, Statement, Custom size (3-7/8" x 5-7/8" to 8-1/2" x 11-3/4")

Cassettes (Opt.): Legal, Letter, Executive, Statement, Custom size (3-7/8" x 5-7/8" to 8-1/2" x 14")

Stack Bypass: Legal, Letter, Executive, Statement, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Custom size (3" x 5" to 8-1/2" x 14")

Supported Media Weights

Cassette: 16 lb. Bond to 36 lb. Bond (60 to 135 g/m²)

Stack Bypass: 16 lb. Bond to 73 lb. Cover (60 to 199 g/m²)

Duplex: 16 lb. Bond to 32 lb. Bond (60 to 120 g/m²)

Print/Copy Speed (BW)

715iF II/715iFZ II: Up to 75 ppm (Letter); Up to 59 ppm (Legal)

615iF II/615iFZ II: Up to 65 ppm (Letter); Up to 51 ppm (Legal)

525iF II/525iFZ II: Up to 55 ppm (Letter); Up to 45 ppm (Legal)

Warm-up Time

From Power On: 30 Seconds or Less⁴

From Sleep

Mode: 10 Seconds or Less

Quick Start-up

Mode: 4 Seconds or Less⁵

Dimensions (W x D x H)

Standard Model: 20-1/4" x 23-5/8" x 24-1/4" (514 mm x 600 mm x 616 mm)

Finisher Model: 20-1/4" x 23-5/8" x 32-1/8" (514 mm x 600 mm x 816 mm)

Dimensions (W x D x H) with Paper Feeding Unit or High Capacity Paper Feeding

Standard Model: 25-1/4" x 26-3/8" x 42-1/4" (641 mm x 670 mm x 1073 mm)

Finisher Model: 25-1/4" x 26-3/8" x 50" (641 mm x 670 mm x 1270 mm)

Installation Space (W x D)

41-3/8" x 32-3/8" (1,052 mm x 823 mm)

Weight⁶

Standard Model: Approx. 81.6 lb. (37 kg)

Finisher Model: Approx. 101.4 lb. (46 kg)

Print Specifications

Print Resolution (dpi)

1200 x 600

Standard Page Description Languages

UFR II, PCL[®]6, Adobe[®] PS[®] 3

Direct Print

Available from USB, Advanced Box, Remote UI, and Web Access⁷

Supported File Types

PDF, TIFF, JPEG, EPS, XPS

Printing from Mobile Devices and Cloud-based Services

A range of software and MEAP-based solutions are available to provide printing from compatible mobile devices or Internet-connected devices and cloud-based services depending on your requirements.⁸

Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese),⁹ Barcode Fonts¹⁰

PS fonts: 136 Roman

Operating System¹¹

UFR II/PS: Windows[®] 7/8.1/10, Windows Server 2008/2008 R2/2012/2012 R2/2016, MAC OS X (10.7 or later)

PCL: Windows[®] 7/8.1/10, Windows Server 2008/2008 R2/2012/2012 R2/2016

Copy Specifications

First-Start-Out Time (LTR)

As fast as 5 Seconds

Copy Resolution (dpi)

Reading: 600 x 600

Printing: 2400 x 600

Multiple Copies

Up to 999

Magnification

25%-400% (1% Increments)

Preset Reductions

25%, 50%, 64%, 78%

Preset Enlargements

129%, 200%, 400%

Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-sided, Density Adjustment, Exposure Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

Special Copy Features

Two-sided Original, Finishing, Job Build, N on 1, Different Size Originals, Density Adjustment, Original Type Selection, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Job Done Notice, Copy ID Card, Skip Blank Pages, Multi Sheet Feed Detection

Scan Specifications

Type

Single-pass Duplexing Automatic Document Feeder

Document Feeder Paper Capacity

100 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

Legal, Letter, Statement

Custom size: 4-1/8" x 5-7/8" to 8-1/2" x 14"

Document Feeder Supported Media Weights

BW Original: 40 to 128 g/m²

Color Original: 64 to 128 g/m²

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height up to 1-1/4"; Weight Up to 4.4 lb. (2 kg)]

Pull Scan

Color Network ScanGear2 for both Twain and WIA

Supported OS: Windows 7/8.1/10/

Server 2008/Server 2008 R2/

Server 2012/Server 2012 R2/Server 2016

Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices or cloud-based services depending on your requirements.

Scan Speed (LTR)

Single-sided Scanning

(Color/BW): 50 ipm/50 ipm (300 dpi);

(Color/BW) 30 ipm/50 ipm (600 dpi)

Double-sided Scanning

(Color/BW): 100 ipm/100 ipm (300 dpi);

(Color/BW) 50 ipm/100 ipm (600 dpi)

Send Specifications

Destination

Email/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax, IP Fax (Optional)

Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Communication Protocol

File: FTP, SMB v3.0, WebDAV

Email/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply Policy, Optimize for Web, PDF A/1-b, Encrypted), XPS (Compact, Searchable), Office Open XML (PowerPoint[®], Word), Digital Signature (PDF/XPS)

Optional: PDF (Trace & Smooth), PDF/XPS (User Signature)

Universal Send Features

Original Type Selection, Two-sided Original, Different-size Originals, Density Adjustment, Sharpness, Erase Frame, Job Build, Sender's Name (TTI), Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-To, Email Priority, TX Report, Original Content Orientation, Skip Blank Originals, Multi Sheet Feed Detection

Fax Specifications

Maximum Number of Connection Lines

One

Modem Speed

Super G3: 33.6 Kbps
G3: 14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size

Statement to Legal

Fax Memory

Up to 30,000 Pages

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast

Max. 256 Addresses

Memory Backup

Yes

Fax Features

Original Type Selection, Two-sided Original, Density for Scanning, Sharpness, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Multi Sheet Feed Detection

Store Specifications

Mail Box Simple (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV Supported

Client PC: Windows (Windows 7/8.1/10)

Concurrent Connections (Max.)

SMB: 64

WebDAV: 3 (Active Sessions)

Advanced Box Available Disc Space

Approx. 16 GB

Advanced Box Features

Disabling Advanced Box, Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

Memory Media

Standard: USB

Security Specifications

Authentication

Standard: Universal Login Manager (Device and Function Level Log-in), User Authentication, Department ID, Authentication, Access Management System, uniFLOW Online Express²

Optional: uniFLOW and uniFLOW Online

Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated)

Optional: Data Loss Prevention (Requires uniFLOW)

Network

Standard: IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP

Document

Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature, Secure Watermark

Optional: User Signature

Environmental Specifications

Operating Environment

Temperature: 50 to 86 °F

Humidity: 20 to 80 % RH (no condensation)

Power Requirements

120-127V, 60 Hz, 9.7 A

Plug (Main Unit)

NEMA 5-15P

Power Consumption

Maximum: Approx. 1.5 kW

Standby: Approx. 29.77 W

Sleep Mode: Approx. 0.41 W¹³

Typical Electricity Consumption (TEC) Rating:

715iF II/715iFZ II: 3.1 kWh

615iF II/615iFZ II: 2.5 kWh

525iF II/525iFZ II: 2.1 kWh

Standards

ENERGY STAR® Certified

Rated EPEAT® Gold³

Consumables

Toner

T03 Black (All-in-One Toner Cartridge)¹⁴

Toner Yield¹⁵

51,500 Images

¹ Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions.

² Requires additional option.

³ For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.

⁴ Time from device power-on until copy ready (not print reservation).

⁵ Time from device power-on to when copy icon appears on the main menu of touch-panel.

⁶ Includes consumables.

⁷ PDF print from Web sites is supported.

⁸ For more information, including compatibility, please visit <https://www.usa.canon.com/mobile-app>.

⁹ Requires the optional PCL International Font Set-A1.

¹⁰ Requires the optional Barcode Printer Kit-D1.

¹¹ Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

¹² No charge for this solution; however activation is required.

¹³ 0.41 W sleep mode not available in all circumstances due to certain settings.

¹⁴ Includes toner, drum, developer, and waste toner hopper.

¹⁵ Toner cartridge yield in accordance with ISO/IEC 19752.

For detailed specifications and a comprehensive list of optional accessories, see the [imageRUNNER ADVANCE 715iF II Series Specifications document](#).

For more information, call or visit
1.800.815.4000 CSA.CANON.COM



Canon
CANON SOLUTIONS AMERICA

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Print speed is based on internal testing. Print speed may vary depending on the number of copies selected, as well as on the settings for size, type, and orientation of paper. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon representative for details. Products shown with optional accessories. Canon U.S.A. and Canon Solutions America, Inc. do not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.
©2018 Canon U.S.A., Inc. All rights reserved.

CSA-18-496
1018-CSAIRA715iFISB-PDF-IH

UFP UNIFIED FIRMWARE PLATFORM



CANON GENUINE
TONER, CARTRIDGE & PARTS

