

PRODUCT SPECIFICATIONS

imageRUNNER ADVANCE C3330i shown



Booklet Finisher-U1



Staple Finisher-U1



Inner 2-way Tray-J1




Inner Finisher-G1



Cassette Feeding Unit-AL1



Utility Tray-A2



Copy Tray-J2



Cabinet Type-J

MAIN UNIT

System Type

Color Digital Multifunction Imaging System

Functions

Standard: Copy, Print (UFR II, PCL 5c/6, Adobe® PostScript® 3™), Scan, Send
Optional: Fax (Up to 2 Lines)

Operation Panel: 7" WVGA Full-Color TFT Screen

Memory

Standard: 2 GB RAM
Maximum: 2 GB RAM

Hard Disk Drive

Standard: 215 GB
Maximum: 215 GB

Network Interface Connection

Standard: 1000Base-TX/100Base-TX/10Base-T
Optional: Wireless LAN (IEEE 803.1x via third-party adapter)

Other Interface

Standard: USB 2.0 (Host) x 2, USB 2.0 (Device)
Optional: Device Port [USB 2.0 (Host) x 2], Copy Control Interface

Copy/Print Speed (BW/Color)

Letter: C3330i: Up to 30/30 ppm
C3325i: Up to 25/25 ppm
Legal/11" x 17": Up to 15 ppm

First-Copy-Out Time (Letter)

As fast as 5.9 Seconds (BW), 8.2 Seconds (Color)

Paper Sources (20 lb. Bond)

Standard: Two 550-sheet Paper Cassettes
100-sheet Stack Bypass

Optional: Dual 550-sheet Paper Cassettes

Maximum: 2,300 Sheets

Output Paper Capacity (20 lb. Bond)

Standard: 250 Sheets (Inner Tray)
Maximum: 2,100 Sheets (w/Staple Finisher or Booklet Finisher)

Output Paper Sizes

Cassette 1: Statement, Letter, Executive, Envelope (ISO-C5), Custom Size (5-1/2" x 7-1/8" to 11-3/4" x 8-1/2")

Cassette 2: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement, Executive, Custom Size (5-1/2" x 7-1/8" to 12" x 18"), Envelopes (COM10 No.10, Monarch, DL)

Cassettes 3/4: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement, Executive, Custom Size (5-1/2" x 7-1/8" to 12" x 18")

Bypass: 12" x 18", 12-5/8" x 17-11/16", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18"), Envelopes (COM10 No.10, Monarch, DL, ISO-C5)

Acceptable Paper Weights

Cassettes: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)
Bypass: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)

Duplexing

Paper Size: Standard Automatic Trayless Duplexing (Executive to 12" x 18")

Paper Weight: 14 lb. Bond to 80 lb. Cover (220 g/m²)

Special Media Support

Tracing, Coated, Labels, Transparency, Pre-punched, Bond, and Envelopes

Envelope Feeding Attachment

Paper Capacity: Up to 50 Sheets (or 45 mm in height)

Acceptable Envelope Type: COM10 No.10, Monarch, DL, ISO-C5

Feeding Speed: 10 cpm

Warm-up Time

From Power On: Approximately 34 Seconds

From Sleep: Approximately 10 Seconds

Quick Startup Mode: Within 7 Seconds*

Power Requirements/Plug

120 V AC, 60 Hz, 7.5 A/NEMA 5-15P

Power Consumption

Maximum: 1.5 kW

Sleep Mode: 0.8 W

Dimensions (H x W x D)

34-5/8" x 22-1/4" x 27-5/16"
(878 mm x 565 mm x 693 mm)

Installation Space (W x D)

35-1/4" x 44" (894 mm x 1117 mm)
(when the Multi-purpose Tray is extended.)

Weight: Approximately 163.4 lb. (74.1 kg)**

Toner (Estimated Yield @ 5% Coverage)

Black: 36,000 Images

Color: 19,000 Images

MAIN UNIT (CONTINUED)

Image Reader Unit

Scan Resolution: Up to 600 x 600 dpi

Acceptable Originals (Glass)

Sheet, Book, 3-Dimensional objects [up to 4.4 lb. (2 kg)]

Maximum Original Size: Up to 11" x 17"

Document Feeder

Scan Method: Duplex Automatic Document Feeder

Acceptable Originals

Paper Sizes: 11" x 17", Legal, Letter, Letter-R, Statement, or Statement-R

Paper Weights: 13 lb. Bond to 34 lb. Bond (50 to 128 g/m²)

Scan Speed (BW and Color; Letter)

Simplex: Up to 55 ipm (300 dpi)
Up to 30 ipm (600 dpi)

Duplex: Up to 27.5 ipm (300 dpi)
Up to 15 ipm (600 dpi)

Paper Capacity: Up to 100 Sheets (20 lb. Bond)

Copy Specifications

Multiple Copies: 1 to 999

Copy Exposure: Automatic or Manual (9 Levels)

Magnification

25% - 400% (1% Increments)

Preset Reductions: 25%, 50%, 64%, 73%, 78%

Preset Enlargements: 121%, 129%, 200%, 400%

Basic Copy Features

Preset R/E Ratios by Area, Finishing, Two-Sided, Exposure Adjustment, Original Type Selection, Interrupt Mode, Sample Set, Setting Confirmation/Cancel, Standard Keys, Reset, Guide Display, Job Duration Display, Reserved Copying, ID Management, Counter Check

Special Copy Features

Two-page Separation, Cover/Sheet Insertion, Booklet, Transparency Interleaving, Shift, Margin, Frame Erase, Image Combination, Different Size Original, Job Build, Job Done Notice, Scan Image Check, Mode Memory, Recall, Negative/ Positive Inversion, Image Repeat, Mirror Image, Sharpness, Secure Watermark, Page Numbering, Copy Set Numbering, Watermark and Date, Document Scan Lock, Area Designation, ID Card Copy

Print Specifications

Processor: Canon Dual Custom Processor (Shared)

Memory

Standard: 2 GB RAM

Maximum: 2 GB RAM

Hard Disk Drive

Standard: 215 GB

Maximum: 215 GB

Engine Resolution: 1200 x 1200 dpi (Max.)

PDL Support

Standard: UFR II, PCL 5c/6, Adobe PS 3

Print Driver Supported OS

UFR II, PCL 5c/6, Adobe PS 3:
Windows® (XP/Windows Vista®/7/8.1), Windows Server (2003/2003R2/2008/2008R2/2012/2012R2), Windows Terminal Server (2003/2003R2/2008/2008R2/2012/2012R2), Microsoft Clustering Server (2003/2003R2/2008/2008R2/2012/2012R2), Citrix (Presentation Server 4.5, XenApp 5.0/6.0/6.5/7.5, XenDesktop 4.0/5.0/5.5/5.6/7.0/7.1/7.5), VMware (vSphere 4/5/5.1), SAP (P53, PCL), Macintosh® (OS X 10.5.8 or later)

Direct Print Support

Standard: TIFF, JPEG, PDF, EPS, *** XPS*

Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Black-and-White Printing, Objective, Color/Black-and-White Auto Detect, Toner Reduction, Poster Printing

Scan Specifications

Network TWAIN Scan: Standard

Network Scan Utility: Color Network ScanGear

Universal Send Specifications

Sending Method

E-Mail, I-Fax, File Server (FTP, SMB, WebDAV), Super G3 Fax (Optional)

Color Mode

Auto Color Select (Color, Gray), Auto Color Select (Color, Black), Full Color, Grayscale, BW

Scan Resolution

600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100 dpi

Address Book Capacity

Max. 1,800 Destinations (Incl. 200 One-Touch Buttons)

Communication Protocol

File: FTP (TCP/IP), SMB (TCP/IP), WebDAV

E-mail/I-Fax: SMTP, POP3, I-FAX (Simple, Full)

File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply Policy, Optimize for Web, PDF A/1-b), XPS (Compact, Searchable), OOXML (.pptx and .docx)

Optional: PDF (Trace & Smooth, Encrypted), PDF/XPS (Digital Signature)

I-Fax Data Format (BW and Color): TIFF (MH, MR, MMR)

Universal Send Features

Two-Sided Original, Different-size Originals, Original Type Selection, Book to Two Pages, Density Adjustment, Sharpness, Document Name, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-to, Sender's Name (TTI), E-Mail Priority

Fax Specifications

Maximum Number of Connection Lines: 2

Modem Speed

Super G3: 33.6 Kbps

G3: 14.4 Kbps

Compression Method: MH, MR, MMR, JBIG

Resolution

400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi

Sending/Recording Size: Statement to 11" x 17"

Fax Features

Job Forwarding, Different-size Originals, Adjusting Overall Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Selecting the Telephone Line (when sending fax), Delayed Send, Preview, Finished Stamp, Job Done Notice, Original Type Selection, Two-sided Original, Book to Two Pages

Store Specifications

Standard: USB Memory, Mail Box Simple

Advanced Box

Store to Remote Advanced Box: Supported

Print/View from Remote Advanced Box: Supported

Security Specifications

Standard

Department ID Management, Single Sign On-H, Access Management System (Device and Function Level Log-in), Secured Print, Trusted Platform Module, IPV6, Restricting Features (Restricting the Send Function, Restricting New Addresses on Address Book), SSL Encrypted Communication, SNMPv1/v3, MAC/IP Address Filtering, SMTP Authentication, POP Authentication before SMTP, HDD Format, HDD Initialize (Up to 9x), HDD Erase (Up to 3x), HDD Lock, IPsec, Adobe® LiveCycle® Rights Management ES2.5 Integration

Optional

Removable HDD, HDD Encryption, HDD Data Erase Scheduler, Encrypted Secure Print, Encrypted PDF, Document Scan Lock, Secure Watermark, IEEE 2600.1 Common Criteria Certification**

Environmental Information

ENERGY STAR® Qualified

Rated EPEAT Silver

EU RoHS Compliant

Ecomark

Blue Angel

WEEE Directive

OPTIONAL ACCESSORIES

Paper Supply Options

Cassette Feeding Unit-AL1

Paper Capacity

550 Sheets x 2 Cassettes [20 lb. Bond (80 g/m²)]

Acceptable Paper Weight

14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)

Acceptable Paper Size

12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement-R, Executive, and Custom Size [5-1/2" x 7-1/8" to 12" x 18" (139.7 mm x 182 mm to 304.8 mm x 457.2 mm)]

Power Source/Maximum Power Consumption

From the Main Unit/Approximately 30 W

Dimensions (H x W x D)

9-13/16" x 22-1/4" x 24-1/4"
(248 mm x 565 mm x 615 mm)

Weight: Approximately 35.5 lb. (16.1 kg)

Cabinet Type-J

Dimensions (H x W x D)

9-13/16" x 22-1/4" x 24-1/4"
(248 mm x 565 mm x 615 mm)

Weight: 42 lb. (19.05 kg)

Output Options

Inner 2-way Tray-J1

Number of Trays: 2

Total Output Capacity

Top Tray: 250 Sheets (20 lb. Bond)

Lower Tray: 100 Sheets (20 lb. Bond)

Acceptable Paper Weight

14 lb. Bond to 140 lb. Index (64 to 256 g/m²)

Acceptable Paper Size

12" x 18", 12-5/8" x 17-11/16", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size [3-7/8" x 5-1/2" to 12-5/8" x 18" (99 mm x 139.7 mm to 320 mm x 457.2 mm)], and Envelopes

Dimensions (H x W x D)

3" x 16-3/4" x 16-1/16"
(76 mm x 427 mm x 407 mm)

Weight: Approximately 1.3 lb. (574 g)

Inner Finisher-G1

Number of Trays: 2 Trays

Total Output Capacity

600 Sheets

Top Tray: 100 Sheets (Letter)

Lower Tray: 500 Sheets (Letter)

Dimensions (H x W x D)

7-7/16" x 23-13/16" x 20-11/16"
188 mm x 604 mm x 525 mm
(When the Auxiliary Tray is extended)

Installation Space (W x D)

40-7/16" x 27-5-16" (1,026 mm x 693 mm)
(when the Multi-Purpose Tray is extended)

Weight: Approximately 15.9 lb. (7.2 kg)

Staple Mode

Acceptable Paper Weight

14 lb. Bond to 140 lb. Index (52 to 256 g/m²)

Acceptable Paper Size

12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size [3-7/8" x 5-1/2" to 12-5/8" x 18" (99 mm x 139.7 mm to 320 mm x 457.2 mm)], and Envelopes

Staple Positions

Corner Stapling (All 4 Corners):
11" x 17", Legal, Letter, Letter-R, Executive

Double Stapling:
11" x 17", Legal, Letter, Letter-R, Executive

Maximum Stapling Capacity

Letter and Executive:
50 Sheets (14 to 21 lb. Bond)
30 Sheets (22 to 28 lb. Bond)
2 Sheets (29 lb. Bond to 140 lb. Index)

11" x 17", Legal, and Letter-R:
30 Sheets (17 to 21 lb. Bond)
20 Sheets (22 to 28 lb. Bond)
2 Sheets (29 lb. Bond to 140 lb. Index)

Paper Capacity of Staple Mode

Top Tray: Not supported for Staple
Lower Tray
Letter and Executive: 30 Sets (or 2-1/16" in height)
11x17, Legal, and Letter-R: 30 Sets (or 1-1/16" in height)
With different paper sizes: 30 Sets (or 1-1/16" in height)
Type of Staple: Staple-P1 (5,000 x 2)

Staple-Free Mode

Acceptable Paper Weight

14 lb. Bond to 28 lb. Bond

Acceptable Paper Size

Letter, Executive, Legal, Letter-R, 11" x 17"

Staple Positions: Corner (All 4 Corners)

Maximum Stapling Capacity

5 Sheets (14 to 17 lb. Bond)
4 Sheets (18 to 21 lb. Bond)
3 Sheets (22 to 28 lb. Bond)

Staple On Demand

Maximum Stapling Capacity

40 Sheets (20 lb. Bond)

Power Source/Maximum Power Consumption

From the Main Unit/Approximately 36 W

Staple Finisher-U1+++

Number of Trays: 2

Total Output Capacity

2,100 Sheets (Letter, Statement, Statement-R, Executive)

Top Tray: 1,000 Sheets (Letter, Statement, Statement-R, Executive) 500 Sheets (12" x 18", 11" x 17", Legal, Letter-R)

Lower Tray: 1,000 Sheets (Letter, Statement, Statement-R, Executive) 500 Sheets (12" x 18", 11" x 17", Legal, Letter-R)

Inner Tray: 100 Sheets

Acceptable Paper Weight

14 lb. Bond to 140 lb. Index (52 to 256 g/m²)

Acceptable Paper Size

12" x 18", 12-5/8" x 17-11/16", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size [3-7/8" x 5-1/2" to 12-5/8" x 18" (99 mm x 139.7 mm to 320 mm x 457.2 mm)], and Envelopes

Staple Positions

Corner Stapling (All 4 Corners):
11" x 17", Legal, Letter, Letter-R, Executive

Double Stapling:
11" x 17", Legal, Letter, Letter-R, Executive

Maximum Stapling Capacity

Letter and Executive:
50 Sheets (14 to 21 lb. Bond) (52 to 81 g/m²)
30 Sheets (22 to 28 lb. Bond) (82 to 105 g/m²)
2 Sheets (29 lb. Bond to 140 lb. Index) (106 to 220 g/m²)

11" x 17", Legal, and Letter-R:
30 Sheets (14 to 21 lb. Bond) (64 to 81 g/m²)
20 Sheets (22 to 28 lb. Bond) (82 to 105 g/m²)
2 Sheets (29 lb. Bond to 140 lb. Index) (106 to 220 g/m²)

Paper Capacity of Staple Mode

Letter and Executive: 50 Sets (or 5-3/4" in height)
11" x 17", Legal, and Letter-R: 50 Sets (or 2-7/8" in height)
With different paper sizes: 50 Sets (or 2-7/8" in height)

Type of Staple: Staple-J1 (5,000 x 3)

Power Source/Maximum Power Consumption

From the Main Unit/Approximately 106 W

Dimensions (H x W x D)

38-1/4" x 26-1/8" x 25-1/2"
[971 mm x 662 mm x 646 mm
(When the Auxiliary Tray is extended)]

Weight: Approximately 89.3 lb. (40.5 kg)

Installation Space

61-1/2" x 27-5/16" (1561 mm x 693 mm)
(When the Multi-Purpose Tray is extended)

OPTIONAL ACCESSORIES (CONTINUED)

Booklet Finisher-U1***

Number of Trays: 2

Total Output Capacity

2,100 Sheets (Letter, Statement-R, Executive)

Top Tray: 1,000 Sheets (Letter, Statement-R, Executive)
500 Sheets (11" x 17", Legal, Letter-R)

Lower Tray: 1,000 Sheets (Letter, Statement-R, Executive)
500 Sheets (11" x 17", Legal, Letter-R)

Inner Tray: 100 Sheets

Acceptable Paper Weight

14 lb. Bond to 140 lb. Index (52 to 256 g/m²)

Acceptable Paper Size

12" x 18", 12-5/8" x 17-11/16", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size [3-7/8" x 5-9/16" to 12-5/8" x 18" (99 x 139.7 mm to 320 mm x 457.2 mm)], and Envelopes

Staple Positions

Corner/Double Stapling:

11" x 17", Legal, Letter, Letter-R, Executive

Saddle-Stitch: 11" x 17", Legal, Letter-R

Maximum Stapling Capacity

Letter and Executive:

50 Sheets (18 to 22 lb. Bond) (64 to 81 g/m²)

30 Sheets (22 to 28 lb. Bond) (82 to 105 g/m²)

2 Sheets (29 lb. Bond to 140 lb. Index)
(106 to 256 g/m²)

11" x 17", Legal, and Letter-R:

30 Sheets (14 to 21 lb. Bond) (52 to 81 g/m²)

20 Sheets (22 to 28 lb. Bond) (82 to 105 g/m²)

2 Sheets (29 lb. Bond to 140 lb. Index)

Paper Capacity of Staple Mode

Letter and Executive: 50 Sets (or 5-3/4" in height)

11" x 17", Legal, and Letter-R: 50 Sets (or 2-7/8" in height)

With different paper sizes: 50 Sets (or 2-7/8" in height)

Maximum Saddle-Stitch Capacity

16 Sheets (16 to 21 lb. Bond)

10 Sheets (22 to 28 lb. Bond)

Paper Capacity of Saddle-Stitch Mode

25 Booklets (5-sheet Booklets)

Type of Staple

Staple-J1 (5,000 x 3)

Staple Cartridge-D2 (2,000 x 3) for saddle-stitch

Power Source/Maximum Power Consumption

From the Main Unit/Approximately 220 W

Dimensions (H x W x D)

38-1/4" x 30-3/8" x 25-7/8"

[971 mm x 771 mm x 656 mm

(When the Auxiliary Tray is extended)]

Weight: Approximately 149 lb. (67.5 kg)

Installation Space

65-3/4" x 27-5/16" (1670 mm x 693 mm)

(When the Multipurpose Tray is extended)

Other Optional Accessories

- Copy Tray-J2
- Utility Tray-A2
- USB Keyboard
- Universal Keyboard Stand-A1
- Copy Card Reader-F1
- Convenience Stapler-B1
- Universal Send Trace and Smooth PDF Kit-A1
- Universal Send Security Feature Set-D1
- Super G3 FAX Board-AR1
- Super G3 2nd Line Fax Board-AR1
- Remote FAX Kit-A1
- Barcode Printing Kit-D1
- Web Access Software-H1
- USB Device Port-E4
- Copy Control Interface Kit-A1
- iR-ADV Security Kit-L1 for IEEE 2600.1 Common Criteria Certification**

* If "Quick Startup Settings for Main Power" is set to ON, it takes 7 seconds until the key operation on the touch panel display is available after turning on the main power.

** Includes consumables.

*** EPS can be printed directly only from Remote User Interface.

* XPS cannot be printed directly from the Web Access software.

** Specified configurations and settings need to be applied to the device in order to achieve and maintain IEEE 2600.1 Common Criteria Certification. Not available at launch. Contact your Canon Authorized Dealer for more information.

*** Requires Cassette Feeding Unit-AL1. Cannot be installed with Cabinet Type-J. Staple Finisher-U1 and Booklet Finisher-U1 cannot be installed at the same time and cannot be installed with Inner Finisher-G1.

NOTE: Some accessories require additional equipment or may be prerequisites for other options. Some accessories cannot be installed simultaneously. Check with your Canon Authorized Dealer for details.

WWW.USA.CANON.COM/SIMPLYADVANCED



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has qualified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon, imageRUNNER, MEAP, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. imageWARE is a registered trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain other countries. All other referenced product names and marks are trademarks of their respective owners. Specifications and availability subject to change without notice. All printer output images are simulated. Not responsible for typographical errors.
©2015 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.

0415-C3330i SRS-PDF-NR

