

PRODUCT SPECIFICATIONS



Not Shown

- 2/3-Hole Puncher Unit-A1 (for External Finishers)

Main Unit

Type

Color Laser Multifunctional

Core Functions

Standard: Print, Copy, Scan, Send, Store
 Optional: Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

Memory

3.0 GB RAM

Hard Disk Drive

Standard: 250 GB

Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T,
 Wireless LAN (IEEE 802.11 b/g/n)

Others

Standard: USB 2.0 x1 (Host), USB 3.0 x1 (Host),
 USB 2.0 x1 (Device)

Optional: Serial Interface, Copy Control Interface

Paper Capacity (LTR, 20 lb. Bond)

Standard: 1,200 Sheets

Maximum: 2,300 Sheets

Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 550-sheet Paper Cassettes, 100-sheet
 Stack Bypass

Optional: Dual 550-sheet Paper Cassettes
 (CASSETTE FEEDING UNIT-AP1),

Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets

Maximum: 3,450 Sheets
 (with External Finisher and Copy Tray)

Finishing Capabilities

Standard: Collate, Group

With Inner Shift

Sorter: Collate, Group, Offset

With Inner
 Finisher: Collate, Group, Offset, Staple, Staple-Free
 Staple, Staple On Demand

With External
 Finishers: Collate, Group, Offset, Staple, Booklet, Staple-
 Free Staple, Staple On Demand, Hole Punch
 (Optional)

Supported Media Types

Paper

Cassettes (1/2): Thin, Plain, Recycled, Color, Heavy,
 Pre-punched, Bond, Transparency, Envelope

Stack Bypass: Thin, Plain, Recycled, Color, Heavy,
 Pre-punched, Labels, Bond, Coated,
 Transparency, Tracing, Envelope

Cassette

Feeding Unit-AP1: Thin, Plain, Recycled, Color, Heavy,
 Pre-punched, Bond, Transparency

Supported Media Sizes

Paper: Letter, Executive, Statement-R, Envelope
 Casette 1: [No.10 (COM10), DL, ISO-C5], Custom Size
 (5-1/2" x 7-1/8" to 11-3/4" x 8-1/2")

Paper Cassette 2: 12" x 18", 11" x 17", Legal, Letter, Letter-R,
 Executive, Statement-R, Envelope
 [No.10 (COM10), Monarch, DL], Custom Size
 (5-1/2" x 7-1/8" to 12" x 18")

Stack Bypass: 12" x 18", 11" x 17", Legal, Letter, Letter-R,
 Executive, Statement, Statement-R,
 Envelope [No.10 (COM10), Monarch,
 DL, ISO-C5], Envelope Custom Size
 (3-7/8" x 3-7/8" to 12-5/8" x 18"),
 Custom Size (3-7/8" x 5-1/2" to
 12-5/8" x 18"), Free Size (3-7/8" x 5-1/2" to
 12-5/8" x 18")

Cassette 12" x 18", 11" x 17", Legal, Letter, Letter-R,
Feeding Executive, Statement-R, Custom Size (5-
Unit-API: 1/2" x 7-1/8" to 12" x 18")

Supported Media Weights

Cassettes: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)
Stack Bypass: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)
Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)

Print/Copy Speed (BW and Color)

C3530i II: Up to 30 ppm (Letter)
Up to 20 ppm (Letter-R)
Up to 15 ppm (Legal)
Up to 15 ppm (11" x 17")
C3525i II: Up to 25 ppm (Letter)
Up to 20 ppm (Letter-R)
Up to 15 ppm (Legal)
Up to 15 ppm (11" x 17")

Warm-up Time

From Power On: 34 Seconds
From Sleep: 10 Seconds
Mode:
Quick Start-up: 10 Seconds¹
Mode:

Dimensions (W x D x H)

22-1/4" x 29-1/4" x 45-1/5" (565 mm x 742 mm x 1148 mm)²

Installation Space (W x D)

Basic: Stack Bypass + Cassette drawers open:
38-1/2" x 44-1/4" (978 mm x 1123 mm)²
Fully Configured: 63-3/4" x 44-1/4" (1620 mm x 1123 mm)³

Weight

Approx. 213.9 lb. (97 kg)⁴

Print Specifications

Print Resolution (dpi)

1200 x 1200

Standard Page Description Languages

UFR II, PCL[®]6, Adobe[®] PS[®] 3

Direct Print

Available from USB, Advanced Box, Remote UI,
and Web Access⁵

Supported File Types

PDF, TIFF, JPEG, EPS, XPS

Printing from Mobile Devices and Cloud-based Services

A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internet-connected devices and cloud-based services depending on your requirements.

Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T (Japanese,
Korean, Simplified and Traditional Chinese),⁶
Barcode Fonts⁷

PS fonts: 136 Roman

Operating System⁸

UFR II/PS: Windows Vista[®]/Server 2008/Windows[®] 7/
Server 2008 R2/Server 2012/Windows 8.1/
Server 2012 R2/Windows 10/Server 2016,
MAC OS X (10.7 or later)

PCL: Windows Vista/Server 2008/Windows 7/
Server 2008 R2/Server 2012/Windows 8.1/
Server 2012 R2/Windows 10/Server 2016

Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Forced Hold Printing, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Toner Reduction

Copy Specifications

First Copy-Out Time (Letter)

As fast as 5.9 seconds (BW)/8.2 seconds (Color)

Multiple Copies

Up to 999 copies

Copy Exposure

Automatic or Manual (9 Levels)

Magnification

25%-400% (1% Increments)

Preset Reductions

25%, 50%, 64%, 73%, 78%

Preset Enlargements

121%, 129%, 200%, 400%

Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

Special Copy Features

Book to Two Pages, Two-Sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different-Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Job Done Notice, Mirror Image, Copy ID Card, Multi Sheet Feed Detection, Free Size Original, Adjust One-Touch Color, Color Balance, Area Designation

Scan Specifications

Type

Single-pass Duplexing Automatic Document Feeder

Document Feeder Paper Capacity

150 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R

Document Feeder Supported Media Weights

BW Original: 13 lb. Bond to 58 lb. Cover (50 to 157 g/m²)
CL Original: 17 lb. Bond to 58 lb. Cover (64 to 157 g/m²)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Up to 4.4 lb. (2 kg)]

Pull Scan

Color Network ScanGear2 for both Twain and WIA
Supported OS: Windows Vista/7/8.1/10/
Server 2008/Server 2008 R2/
Server 2012/Server 2012 R2/Server 2016

Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

Scan Speed (Letter)

Single-sided Scanning (BW/Color):
80 ipm (300 dpi)/51 ipm (600 dpi)
Double-sided Scanning (BW/Color):
160 ipm (300 dpi)/51 ipm (600 dpi)

Send Specifications

Destination

Email/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box,
Super G3 Fax (Optional), IP Fax (Optional)

Color Mode

Automatic-Color Select (Full Color/Grayscale), Automatic-Color Select (Full Color/Black-and-White), Full color, Grayscale, and Black-and-White

Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Communication Protocol

File: FTP, SMB, WebDAV
Email/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

File Format

Standard: TIFF, JPEG, PDF (Encrypted, Compact, Searchable, Apply Policy, Optimize for Web, PDF A/1-b, Office Open XML (PowerPoint[®], Word), Digital Signature (PDF/XPS)
Optional: PDF (Trace & Smooth)

Universal Send Features

Original Type Selection, Two-Sided Original, Book to Two Pages, Different-Size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-To, Email Priority, TX Report, Original Content Orientation, Skip Blank Originals, Multi Sheet Feed Detection

Fax Specifications

Maximum Number of Connection Lines

2

Modem Speed

Super G3: 33.6 Kbps
G3: 14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size

Statement-R to 11" x 17"

Fax Memory

Up to 30,000 Pages

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast

Max. 256 Addresses

Memory Backup

Yes

Fax Features

Original Type Selection, Two-Sided Original, Book to Two Pages, Different-Size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Sender's Name (TTI), Select Line, Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, TX Report, Multi Sheet Feed Detection

Store Specifications

Mail Box Simple (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV
Supported Windows (Windows Vista/7/8/8.1/10)
Client PC:
Concurrent Connections (Max.)
SMB: 64
WebDAV: 3 (Active Sessions)

Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD)

Advanced Box Features:

Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

Memory Media

Standard: USB

Security Specifications

Authentication

Standard: Universal Login Manager, uniFLOW Online Express,^{9,10} User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in
Optional: uniFLOW

Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated)
Optional: Hard Disk Drive Removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Network

Standard: Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP

Document

Standard: Secure Watermark, Encrypted PDF, Encrypted Secure Print, Digital Signatures, Adobe LiveCycle® Rights Management ES2.5 Integration
Optional: User Signatures, Document Scan Locking

Environmental Specifications

Operating Environment

Temperature: 50 to 86 °F
Humidity: 20 to 80 % RH (no condensation)

Power Requirements

120-127V AC 60 Hz, 7.5 A

Plug (Main Unit)

NEMA 5-15P

Power Consumption

Maximum: Approx. 1.5 kWh
Standby: Approx. 44.1 W
Sleep Mode: Approx. 0.8 W¹¹
Typical Electricity Consumption (TEC) Rating:
C3530i II: 1.2 kWh
C3525i II: 1.0 kWh

Standards

ENERGY STAR® Certified
Rated EPEAT® Gold¹²

Consumables

Toner

GPR-53 Toner¹³

Toner Yield (Estimated @ 5% Coverage)

Black: 36,000 Images
Color (C,M,Y):¹³ 19,000 Images

Paper Supply Options

CASSETTE FEEDING UNIT-A1

Paper: 550 Sheets x 2 Cassettes
Capacity: [20 lb. Bond (80 g/m²)]
Paper Size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, and Custom Size [5-1/2" x 7-1/8" to 12" x 18" (139.7 x 182.0 to 304.8 x 457.2 mm)]
Paper Weight: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)

Power Source: From the Main Unit
Dimensions: 22-1/4" x 24-1/4" x 9-3/4"
(W x D x H): (565 mm x 615 mm x 248 mm)
Weight: Approx. 35.3 lb. (16 kg)

Output Options

INNER 2-WAY TRAY-J1

Number of Trays: 2
Total Output Capacity: Upper Tray: 100 Sheets
Lower Tray: 250 Sheets
Paper Weight: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)
Paper Size: Standard size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Envelope Custom Size (3-7/8" x 3-7/8" to 12-5/8" x 18")
Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18")
Dimensions: 16-7/8" x 16" x 3"
(427 mm x 407 mm x 76 mm)
Weight: Approx. 1.3 lb (0.6 kg)

INNER SHIFT SORTER-A1

Number of Trays: 1
Tray Capacity: Letter/Executive (250 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R/Statement/Statement-R (125 Sheets)
Paper Weight: 14 lb. Bond to 110 lb. Index (52 to 300 g/m²)
Paper Size: Non-Sort: 12"x18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Envelope Custom Size: 3-7/8" x 3-7/8" to 12-5/8" x 18", Custom Size: 3-7/8" x 5-1/2" to 12-5/8" x 18"
Shift: 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R
Dimensions: 21-1/4" x 20-5/8" x 4-1/2"
(W x D x H): (538 mm x 523 mm x 114 mm)
Weight: Approx. 6.6 lb (3.0 kg)

INNER FINISHER-K1

Number of Trays: 2
Top Tray: Letter/Statement/Statement-R/Executive (100 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (50 Sheets)
Lower Tray: Letter/Statement/Statement-R/Executive (500 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (250 Sheets)
Paper Weight: 14 lb. Bond to 110 lb. Index (52 to 300 g/m²)

Staple Position: Corner, Double
Staple Capacity

Corner Staple and Double Staple
Letter/Executive: 50 Sheets (14 to 24 lb. Bond)
11" x 17"/Legal/Letter-R: 30 Sheets (14 to 24 lb. Bond)
Staple-Free Staple
11"x17"/Letter: 5 Sheets (14 to 17 lb. Bond)
4 Sheets (17.3 to 21.7 lb. Bond)
3 Sheets (21.7 to 28 lb. Bond)

Staple On Demand: 40 Sheets [20 lb. Bond (80 g/m²)]

Power Source: From the Main Unit
Dimensions: 23-3/4" x 20-5/8" x 7-3/8"
(W x D x H): (604 mm x 525 mm x 188 mm)
Weight: Approx. 17.6 lb (8 kg)

STAPLE FINISHER-AA1 (External)

Number of Trays: 2
Top Tray: Letter/Executive/Statement/Statement-R (250 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (125 Sheets)

Lower Tray: Letter/Executive/Statement/Statement-R
Capacity: (3,000 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (1,500 Sheets)

Paper Weight

Top Tray: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)
Lower Tray: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)

Staple Position: Corner, Double

Staple Capacity

Corner Staple and Double Staple

Letter/Executive: 50 Sheets [24 lb. Bond (90 g/m²)]
11" x 17"/Legal/Letter-R: 30 Sheets [24 lb. Bond (90 g/m²)]
Staple-Free Staple:
11"x17"/Letter: 5 Sheets [14 to 17 lb. Bond ((52 to 64 g/m²)]
4 Sheets [17.3 to 21.7 lb. Bond (65 to 81.4 g/m²)]
3 Sheets [21.7 to 28 lb. Bond (81.5 to 105 g/m²)]

Staple On Demand:

50 Sheets [24 lb. Bond (90 g/m²)]

Power Source: From the Main Unit

Dimensions: 25-1/8" x 24-1/2" x 40"
(W x D x H): (637 mm x 623 mm x 1016 mm)
Weight: Approx. 66.1 lb (30 kg)

BOOKLET FINISHER-AA1 (External)

Number of Trays: 2
Top Tray: Letter/Executive/Statement/Statement-R (250 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (125 Sheets)
Lower Tray: Letter/Executive/Statement/Statement-R (3,000 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (1,500 Sheets)

Paper Weight

Top Tray: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)
Lower Tray: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)

Staple Position: Corner, Double

Staple Capacity

Corner Staple and Double Staple

Letter/Executive: 50 Sheets [24 lb. Bond (90 g/m²)]
11" x 17"/Legal/Letter-R: 30 Sheets [24 lb. Bond (90 g/m²)]
Staple-Free Staple
11"x17"/Letter: 5 Sheets [14 to 17 lb. Bond ((52 to 64 g/m²)]
4 Sheets [17.3 to 21.7 lb. Bond (65 to 81.4 g/m²)]
3 Sheets [21.7 to 28 lb. Bond (81.5 to 105 g/m²)]

Staple On Demand:

50 Sheets [24 lb. Bond (90 g/m²)]

Booklet-Stitch

Booklet-Stitch Staple: 20 Sheets x 10 Sets [22 lb. Bond (81 g/m²)]
Paper Size: Custom Size [7-3/4" x 10-5/8" to 12" x 18" (195 mm x 270 mm to 304.8 mm x 457.2 mm)]
Capacity: [including one cover sheet up to 140 lb. Index (256 g/m²)]

Power Source: From the Main Unit
Dimensions: 25-1/8" x 24-1/2" x 40"
(W x D x H): (637 mm x 623 mm x 1016 mm)
Weight: Approx. 116.8 lb (53 kg)

2/3-HOLE PUNCHER UNIT-A1

(Requires either the STAPLE FINISHER-AA1 or BOOKLET FINISHER-AA1)

Acceptable

Punch Paper: 14 lb. Bond to 110 lb. Cover
Weight: (52 to 300 g/m²)

Acceptable Punch Paper Size

Two holes: 11" x 17", Legal, Letter, Letter-R, Executive

Three holes: 11" x 17", Letter, Executive

Power Source: From the Main Unit

Hardware Options

Card Readers

IC CARD READER BOX-C1
MiCARD PLUS PROXIMITY CARD READER
COPY CARD READER-F1
COPY CARD READER ATTACHMENT-B5

Others

CABINET TYPE-R
COPY TRAY-J2
UTILITY TRAY-B1
PLATEN COVER TYPE W
USB KEYBOARD

Security Options

Document Security

DOCUMENT SCAN LOCK KIT-B1
iR-ADV SECURITY KIT-P1 FOR IEEE 2600.1 COMMON
CRITERIA CERTIFICATION¹⁴

Data Security

REMOVABLE HDD KIT-AK2

System and Controller Options

Print Accessories

PCL INTERNATIONAL FONT SET-A1

Barcode Printing

BARCODE PRINTING KIT-D1

System Accessories

SERIAL INTERFACE KIT-K3
COPY CONTROL INTERFACE KIT-A1
CONNECTION KIT-A1 FOR BLUETOOTH LE
NFC KIT-C1
MEAP WEB CONNECTION KIT-G3¹⁵

Fax Accessories

SUPER G3 FAX BOARD-AU1
SUPER G3 2ND LINE FAX BOARD-AU1
REMOTE FAX KIT-A1
IP FAX EXPANSION KIT-B1

Other Options

Accessibility Accessories

ADF ACCESS HANDLE-A1
VOICE GUIDANCE KIT-G1
VOICE OPERATION KIT-D1
BRAILLE LABEL KIT-F1

Staples

STAPLE-P1¹⁶
STAPLE CARTRIDGE-Y1¹⁷

- ¹ Time from device power-on to when copy jobs can be programmed.
² Includes main unit and either Cassette Feeding Unit-AP1 or Cabinet Type-R.
³ Includes main unit and either Cassette Feeding Unit-AP1 or Cabinet Type-R and Staple/Booklet Finisher-AA1.
⁴ Includes main unit, ADF, consumables, and Cassette Feeding Unit-AP1.
⁵ PDF print from Web sites is supported.
⁶ Requires the optional PCL International Font Set-A1.
⁷ Requires the optional Barcode Printer Kit-D1.
⁸ Other operating systems and environments, including AS/400, UNIX, Linux and Citrix, may be supported. Some solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.
⁹ No charge for this solution; however activation is required.
¹⁰ Check for availability.
¹¹ 0.8 W sleep mode not available in all circumstances due to certain settings.
¹² For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.
¹³ GPR-53L Toner also available for Color (C, M, Y). Yield (estimated @ 5% coverage) is 8,500 images.
¹⁴ Will launch at a later date.
¹⁵ No charge for this option; however it does need to be ordered.
¹⁶ Used for corner/double stapling only. 2 cartridges per case. 5,000 staples per cartridge.
¹⁷ Used for booklet finishing only. 2 cartridges per case. 2,000 staples per cartridge.

USA.CANON.COM/SIMPLYADVANCED



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. It indicates that this model has been upgraded to new system software and includes additional security features as standard. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors. ©2018 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.

