

imageRUNNER ADVANCE C7500 III Series

Color | High-volume | Multifunction

Print up to 80/70 ppm (BW/color)

Scan up to 240/220 ipm (300 dpi) (BW/color, duplex)

Print up to 13" × 19"

9,300-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.



WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive!
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.



SECURITY

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party Security Information and Event Management (SIEM) systems to help provide real-time comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alterations or tampering.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.²



QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for consistently striking images, thanks to Canon's V² color profile.
- Designed to achieve maximum uptime with status notifications that help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.



DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



COST MANAGEMENT


- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-the-minute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR® certified and rated EPEAT® Gold.³

CONFIGURATION OPTIONS



SPECIFICATIONS

Main Unit

Type

Color Laser Multifunctional

Core Functions

Standard: Print, Copy, Scan, Send, Store
Optional: Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

Standard: 10.1" TFT LCD WSVGA Color Touch-panel
Optional: 10.4" TFT LCD WSVGA Color Upright-panel

Memory

4.0 GB RAM

Hard Disk Drive

Standard: 250 GB/Maximum: 1 TB

Print Resolution

2400 dpi x 2400 dpi

Interface Connection

Network

Standard: 1000Base-T/100Base-TX/10Base-T,
Wireless LAN (IEEE 802.11 b/g/n)
Optional: NFC, Bluetooth Low Energy

Others

Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),
USB 2.0 x1 (Device)
Optional: Serial Interface, Copy Control Interface

Paper Capacity (LTR, 20 lb. Bond)

Standard: 3,550 Sheets
Maximum: 9,300 Sheets

Paper Sources (LTR, 20 lb. Bond)

Standard: Two 1,100-sheet Paper Drawers,
Two 550-sheet Paper Cassettes,
250-sheet Stack Bypass
Optional: 3,500-sheet Paper Deck (Paper Deck
Unit-E1), 3,500-sheet Paper Deck (POD Deck
Lite-C1), 6,000-sheet Paper Deck (Multi-
Drawer Paper Deck-C1)
Maximum: 9,300 Sheets (With Multi-Drawer Paper
Deck-C1)

Paper Output Capacity (LTR, 20 lb. Bond)

250 Sheets (with Copy Tray-R2)
3,500 Sheets (with External Finisher-V2)
4,250 Sheets (with External Finisher-X1)

Finishing Capabilities

Standard: Collate, Group
With Finishers: Booklet, Hole Punch (multiple patterns),
Staple-Free Staple, Staple on Demand,
Document Insertion, Fold (C-/Z-/Half/
Double parallel/Accordion-Z fold),
Trimming

Supported Media Types

Paper Drawers (1/2): Thin, Plain, Recycled, Color, Heavy,
Pre-punched, Letterhead, Bond,
Transparency
Paper Cassettes (3/4): Thin, Plain, Recycled, Color, Heavy,
Pre-punched, Letterhead, Bond,
Transparency, Tab, Envelope
Stack Bypass: Thin, Plain, Recycled, Color, Heavy,
Pre-punched, Labels, Letterhead,
Bond, Coated, Transparency, Tab,
Tracing,¹ Envelope, Textured

Supported Media Sizes

Paper Drawers (1/2): Letter
Paper (3/4): 13" x 19", 12" x 18", 11" x 17", Legal, Letter,
Cassettes (3/4): Letter-R, Executive, Statement-R, Envelope
[No.10 (COM10), Monarch, DL, ISO-C5],
Custom Size (5-1/2" x 7-1/8" to
13" x 19-1/4"), Envelope Custom Size (3-1/8"
x 5-7/8" to 13" x 19-1/4")
Stack Bypass: 13" x 19", 12" x 18", 11" x 17", Legal, Letter,
Letter-R, Executive, Statement-R, Envelope
[No.10 (COM10), Monarch, DL, ISO-C5],
Custom Size (4" x 5-7/8" to
13" x 19-1/4"), Envelope Custom Size
(3-1/2" x 5-7/8" to 13" x 19-1/4"),
Free Size (4" x 7-1/8" to 13" x 19-1/4")

Supported Media Weights

Paper Drawers: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)
Paper Cassettes: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)
Stack Bypass: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)
Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)

Print/Copy Speed (BW/Color)

C7580i III: Up to 80/70 ppm (Letter); Up to 60/52 ppm
(Letter-R); Up to 47/41 ppm (Legal);
Up to 40/35 ppm (11" x 17")
C7570i III: Up to 70/65 ppm (Letter); Up to 52/48 ppm
(Letter-R); Up to 41/38 ppm (Legal);
Up to 35/32 ppm (11" x 17")
C7565i III: Up to 65/60 ppm (Letter); Up to 48/45 ppm
(Letter-R); Up to 38/35 ppm (Legal);
Up to 32/30 ppm (11" x 17")

Warm-up Time

From Power On: Approx. 30 Seconds⁵
Quick Startup
Mode: Approx. 4 Seconds⁶

Dimensions (W x D x H)

27-1/8" x 37-1/8" x 48" (689 mm x 941 mm x 1220 mm)

Installation Space (W x D)

Basic [With Front Door Open + Stack Bypass/Upper-Right
Cover Open + Buffer Pass+ Booklet Finisher-V2/Extension
Tray and Rotary Tray Extended]:
79-3/4" x 60" (2,026 mm x 1,524 mm)
Fully Configured [With Front Cover Open + Multi-Drawer
Paper Deck-C1 + Buffer Pass + Document Insertion Unit-N1 +
Multi Function Professional Puncher-A1 + Paper Folding
Unit-J1+ Booklet Finisher-X1]:
150-3/8" x 60" (3,818 mm x 1,524 mm)

Weight

Approx. 593 lb. (269 kg)⁷

Print Specifications

Data Processing Resolution (dpi)

Up to 1200 x 1200

Standard Page Description Languages

UFR II, PCL[®]6, Adobe[®] PS[®] 3

Direct Print

Available from USB, Advanced Box, Remote UI,
and Web Access⁸

Supported File Types for Direct Print

PDF, TIFF, JPEG, EPS,⁹ XPS

Printing from Mobile Devices and Cloud-based Services

A range of software and MEAP-based solutions are available
to provide printing from mobile devices or Internet-
connected devices and cloud-based services depending on
your requirements.

Fonts

PCL Fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T (Japanese,
Korean, Simplified and Traditional Chinese),¹⁰
Barcode Fonts¹¹
PS Fonts: 136 Roman

Operating System¹²

UFR II: Windows[®]/Server 2008/Windows[®] 7/
Server 2008 R2/Server 2012/Windows 8.1/
Server 2012 R2/Windows 10/Server 2016,
MAC OS X (10.9 or later)
PCL: Windows/Server 2008/Windows 7/Server
2008 R2/Server 2012/Windows 8.1/Server
2012 R2/Windows 10/Server 2016
PS: Windows Server 2008/Windows 7/Server
2008 R2/Server 2012/Windows 8.1/Server
2012 R2/Windows 10/Server 2016, MAC OS
X (10.7 or later)

Copy Specifications

First-Copy-Out Time (Letter)

C7580i III: As fast as 4.4 seconds (BW)/
5.4 seconds (Color)
C7570i III: As fast as 4.8 seconds (BW)/
5.9 seconds (Color)
C7565i III: As fast as 4.8 seconds (BW)/
5.9 seconds (Color)

Copy Resolution (dpi)

Reading: Up to 600 x 600
Printing: 2400 x 2400

Multiple Copies

Up to 9,999

Magnification

25%-400% (1% Increments)

Preset Reductions

25%, 50%, 64%, 73%, 78%

Preset Enlargements

121%, 129%, 200%, 400%

Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper
Setting, Previous Settings, Favorite Settings, Finishing, Two-
sided, Density Adjustment, Original Type Selection, Interrupt
Mode, Setting Confirmation/Cancel

Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet,
Job Build, N on 1, Add Cover, Insert Sheets, Different-size
Originals, Density Adjustment, Original Type Selection,
Transparency Cover Sheets, Page Numbering, Copy Set
Numbering, Sharpness, Erase Frame, Secure Watermark,
Print Date, Shift, Gutter, Print & Check, Negative/Positive,
Repeat Images, Merge Job Blocks, Job Done Notice, Mirror
Image, Print on Tab, Store in Mail Box, Superimpose Image,
Copy ID Card, Detect Feeder Multi Sheet Feed, Free Size
Original, Color Balance, Adjust One-Touch Color, Area
Designation, Skip Blank Pages

Scan Specifications

Type

Color Platen and Single-pass Duplexing Automatic
Document Feeder

Document Feeder Paper Capacity

300 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R,
Custom Size: 5" x 5-1/2" to 12" x 17"

Document Feeder Supported Media Weights

BW Original: 13 lb. Bond to 80 lb. Cover
(50 to 220 g/m²)
Color Original: 17 lb. Bond to 80 lb. Cover
(64 to 220 g/m²)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height: Up to
2" (50mm), Weight: up to 4.4 lb. (2kg)]

Pull Scan

Color Network ScanGear2 for both Twain and WIA
Supported OS: Windows/7/8.1/10
Server 2008/Server 2008 R2/Server 2012/
Server 2012 R2/Server 2016

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to
mobile devices and cloud-based services depending on
your requirements.

Scan Speed (Letter) (300 dpi/600 dpi)

Single-sided Scanning (BW): 120 ipm/120 ipm
Single-sided Scanning (Color): 120 ipm/70 ipm
Double-sided Scanning (BW): 240 ipm/150 ipm
Double-sided Scanning (Color): 220 ipm/90 ipm

Send Specifications

Destination

Email/Internet Fax (SMTP), SMB v3.0, FTP, WebDAV, Mail
Box, Super G3 Fax (Optional), IP Fax (Optional)

Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,
200 x 100, 150 x 150, 100 x 100

Communication Protocol

File: FTP (TCP/IP), SMB v3.0, WebDAV
Email: SMTP, POP3

File Format

Standard: TIFF, JPEG, PDF (Encrypted, Compact,
Searchable, Apply Policy, Optimize for Web,
PDF A/1-b, Limited Color, Device Signature),
XPS (Compact, Searchable, Device
Signature), Office Open XML (PowerPoint[®],
Word), Encrypted PDF,

Optional: PDF (Trace & Smooth, User Signature), XPS (User Signature)

Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, Email Priority, TX Report, Original Content Orientation, Skip Blank Pages, Detect Feeder Multi Sheet Feed

Fax Specifications

(Optional)

Maximum Number of Connection Lines

4

Modem Speed

Super G3: 33.6 Kbps
G3: 14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size

Statement-R to 11" x 17"

Fax Memory

Up to 30,000 pages

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 dials

Sequential Broadcast

Max. 256 addresses

Memory Backup

Yes

Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Select Line, Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed

Store Specifications

Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV Supported

Client PC: Windows (Windows 7/8.1/10)

Concurrent Connections (Max.)

SMB: 64

WebDAV: 3 (Active Sessions)

Advanced Box Available Disk Space

Approx. 16 GB (Standard HDD)/Approx. 480 GB (1 TB HDD)

Advanced Box Features

Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

Memory Media

Standard: USB

Security Specifications

Authentication

Standard: Universal Login Manager, uniFLOW OnLine Express,¹³ User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in
Optional: uniFLOW

Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup
Optional: Hard Disk Drive Mirroring, Hard Disk Drive Removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Network

Standard: Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

Document

Standard: Secure Watermark, Secure Print, Forced Hold Printing, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature
Optional: User Signature, Document Scan Lock

Environmental Specifications

Power Requirements

C7580i III: 208 - 240 V AC, 60 Hz, 12 A

C7570i III/C7565i III: 120-127 V AC, 60 Hz, 16 A

Plug (Main Unit)

C7580i III: NEMA 6-15P

C7570i III/7565i III: NEMA 5-20P

Power Consumption

Maximum

C7580i III: Approx. 2,500 W

C7570i III/7565i III: Approx. 2,000 W

Standby: Approx. 119.2 W¹⁴

Sleep Mode: Approx. 0.9 W¹⁵
Typical Electricity Consumption (TEC) Rating
C7580i III: 5.2 kWh
C7570i III: 4.6 kWh
C7565i III: 4.5 kWh

Standards

ENERGY STAR® Certified
Rated EPEAT® Gold³

Consumables

Toner

GPR-56 Toner

Toner Yield (Estimated @ 5% Coverage)

Black: 82,000 Images

Color (C,M,Y): 66,500 Images

¹ Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions.

² Requires additional option.

³ For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.

⁴ Some types of tracing paper cannot be used.

⁵ Time from device power-on, until copy ready (not print reservation).

⁶ Time from device power-on to when key operations can be performed on the touch panel display.

⁷ Includes main unit, ADF, and consumables.

⁸ PDF print from Web sites is supported.

⁹ EPS can be printed directly only from the Remote User Interface.

¹⁰ Requires the optional PCL International Font Set-A1.

¹¹ Requires the optional Barcode Printer Kit-D1.

¹² Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

¹³ No charge for this solution; however activation is required.

¹⁴ Reference Value: measured one unit

¹⁵ 0.9 W Sleep mode is not available in all circumstances due to certain settings.

For detailed specifications and a comprehensive list of optional accessories, see the imageRUNNER ADVANCE C7500 III Series Specifications document.

USA.CANON.COM/SIMPLYADVANCED



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors. ©2019 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.



To learn about Canon's many awards, visit usa.canon.com/awards.

