

A4 Multifunction Color

IM C300F**IM C400F****IM C400SRF** Copier Printer Facsimile Scanner

Future-proof technology at your fingertips

At last! A printing system that doesn't stress everyone out. Things have changed. Our new multifunction printer (MFP) is the intelligent device you've always wanted to scan, copy and print your Letter/A4 size documents. This color MFP has a smart touchscreen control panel and is always running the latest technology.

Putting up with old equipment until your contract finally ends is out. Software that automatically updates is in — along with the ability to add additional functionality that your business may need in the future. Your MFP is always ready to operate. You can print, copy and scan more materials — faster and remotely from wherever you are. Just plug in this intelligent device and let it run. You'll be glad to know our A4 and A3 MFP models work in exactly the same way too.

With output speeds ranging from 31-45 Letter-size pages per minute, these devices — along with their optional paper trays — allow you to meet just about any type of print job requirement. Plus, the trays hold more paper than ever before, so you spend less time refilling them. You won't need to budget for extra services or equipment either. Select a model that staples and you'll have every function you need, built into one smart device.

It's the 2020s, and you're right to demand an MFP that can keep up with your dynamic digital workplace.

Scalable document handling options that grow with your business

Modern devices all interact with one another. Why should your MFP be any different? With Lanier, you can not only scan documents to a folder on your network but also add third-party apps and cloud services. You decide which features your device does and doesn't have. You'll only see options for the services you use, so you can get to them quickly and without any fuss.



Secure handling of your documents and data

For complete security across your network, your MFP runs our own operating system. This gives you complete control over who sees and doesn't see the documents you process. Your MFP can overwrite your data at the end of every print run, so no sensitive information is ever leaked. You decide who has access to every document, restricting access to select information.



Sustainable design to take you far into the future

Lanier MFPs are designed to be energy efficient. It's as important to us as it is to you that any device we develop leaves a small carbon footprint on the environment. We also have a deep commitment to minimizing the environmental impact of our devices and workflow, which is why we continually work to meet the global standards for energy and resource efficiency, as defined by EPEAT®* and ENERGY STAR®. Lanier devices have low energy consumption levels, in both Typical Electricity Consumption (TEC) and actual power consumption.

**EPEAT is only applicable in the USA.*



Simple systems to make your working life easier

All our devices operate like one machine, because the control panels and technology are exactly the same. You won't waste time figuring out how to scan or print every time you use another machine. Our 10.1" tilting touchscreen is as intuitive to use as your smartphone, so cryptic control panel messages are now a thing of the past. Add your company logo, personalize your device for different team members and use it to watch how-to videos — or get help online.

Lanier's range of intelligent MFPs works as a fleet, which means you can access all of them at once to keep the whole network running. Many operational issues can easily be fixed remotely, so your machine is never down for long. This allows you to focus on more important things, while your MFP runs effortlessly in the background — like every other smart device you use to grow your business.



IM C300F / IM C400F / IM C400SRF product configuration chart

Models

IM C300F



10.1" Smart Operation Panel
50-sheet SPDF
250-sheet input tray
100-sheet bypass tray
100-sheet output tray
Dimensions: 19.6" x 22.1" x 20.1"
(498 x 561 x 510 mm)
Weight: 103.6 lbs. (47 kg)

IM C400F



10.1" Smart Operation Panel
50-sheet SPDF
550-sheet input tray
100-sheet bypass tray
100-sheet output tray
Dimensions: 19.6" x 22.1" x 23.2"
(498 x 561 x 590 mm)
Weight: 110.2 lbs. (50 kg)

IM C400SRF



10.1" Smart Operation Panel
50-sheet SPDF
550-sheet input tray
100-sheet bypass tray
Internal finisher (250-sheet output /
50-sheet stapling)
Dimensions: 24.2" x 22.1" x 27.8"
(615 x 561 x 706 mm)
Weight: 132.3 lbs. (60 kg)

Configuration Options

Low Cabinet Type V



Dimensions: 19.6" x 20.9" x 9.1"
(498 x 532 x 232 mm)
Weight: 22.8 lbs. (10.3 kg)

Medium Cabinet Type W



Dimensions: 19.6" x 20.9" x 15.0"
(498 x 532 x 380 mm)
Weight: 28.5 lbs. (13 kg)

Tall Cabinet Type X



Dimensions: 19.6" x 20.9" x 20.8"
(498 x 532 x 528 mm)
Weight: 34.3 lbs. (15.6 kg)

Paper Feed Unit PB1170



Capacity: 550 sheets
Dimensions: 19.6" x 21.7" x 5.9"
(498 x 552 x 150 mm)
Weight: 24 lbs. (10.7 kg)
Max 2 optional paper feed units can
be installed without a caster table
Installation of 3 optional paper feed
units requires caster table

1-Bin Tray Type BN1040

Capacity: 100 sheets
Dimensions: 21.8" x 19.0" x 5.5"
(554 x 482 x 139 mm)
Weight: 6.6 lbs. (3 kg)
Not available with the IM C400SRF

NFC Card Reader Type M13

Caster Table Type Y



Dimensions: 19.6" x 20.9" x 3.3"
(498 x 532 x 84 mm)
Weight: 10.1 lbs (4.6 kg)

Other options

Device Server Option Type M37
IEEE 802.11a/g/n Interface Unit Type M19
OCR Unit Type M13
Page Keeper Type M28
PostScript3 Unit Type M41
VM Card Type M37
ESP XG-PCS-15D Power Filter
ESP S1 Power Filter

Dimensions are stated in width x depth x height (W x D x H)



LANIER IM C300F/IM C400F/IM C400SRF

MAIN SPECIFICATIONS

| | IM C300F | IM C400F | IM C400SRF |
|--------------------------------|--|---|---|
| GENERAL | | | |
| Warm-up time | 19 seconds | 17 seconds | 17 seconds |
| First output speed: B/W | 7.2 seconds | 6.2 seconds | 6.7 seconds |
| First output speed: full color | 8.6 seconds | 7.4 seconds | 7.9 seconds |
| Continuous output speed | 31 ppm B/W, color | 45 ppm B/W / 42 ppm color | 45 ppm B/W / 42 ppm color (simplex) / 38 ppm color (duplex) |
| Memory: standard | 2 GB | 2 GB | 2 GB |
| Memory: maximum | 2 GB | 2 GB | 2 GB |
| HDD: standard | 320 GB | 320 GB | 320 GB |
| HDD: maximum | 320 GB | 320 GB | 320 GB |
| Weight | 103.6 lbs. (47 kg) | 110.2 lbs. (50 kg) | 132.3 lbs. (60 kg) |
| Dimensions: W x D x H | 19.6" x 22.1" x 20.1" (498 x 561 x 510 mm) | 19.6" x 22.1" x 23.2" (498 x 561 x 590 mm) | 24.2" x 22.1" x 27.8" (615 x 561 x 706 mm) |
| Power source | 120V – 127V 60 Hz | 120V – 127V 60 Hz | 120V – 127V 60 Hz |
| COPIER (STANDARD) | | | |
| Multiple copying | | Up to 999 copies | |
| Copy resolution: maximum | | 600 x 600 dpi | |
| Zoom | | From 25% to 400% in 1% steps | |
| PRINTER (STANDARD) | | | |
| Printer language: standard | | PCL5c, PCL6, PostScript 3 (emulation), PDF direct (emulation) | |
| Printer language: option | | Genuine Adobe® PostScript®3™, PDF Direct from Adobe® | |
| Print resolution: maximum | | 1,200 x 1,200 / 1 bit | |
| Network interface: standard | | Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host I/F Type A, USB Host I/F Type B | |
| Network interface: option | | Wireless LAN (IEEE 802.11a/b/g/n) | |
| Mobile printing capability | | Apple AirPrint™, Mopria, NFC, RICOH Smart Device Connector | |
| Network protocol | | TCP/IP (IP v4, IP v6) | |
| Windows® environments | | Windows® 7/8.1/10, Windows® Server 2008/2008R2/2012/2012R2, Windows® Server 2016, Windows® Server 2019 | |
| Mac OS environments | | Macintosh OS X Native v10.11 or later | |
| UNIX environments | | UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux Enterprise, IBM® AIX | |
| SAP® environments | | SAP® R/3®, SAP® S/4® | |
| SCANNER (STANDARD) | | | |
| Scanning: B/W | | 41 ipm (simplex) / 82 ipm (duplex) @ 200/300 dpi, Letter size | |
| Scanning: full color | | 41 ipm (simplex) / 82 ipm (duplex) @ 200/300 dpi, Letter size | |
| Resolution: maximum | | 600 dpi (1200 dpi via TWAIN) | |
| Compression method | | B/W: TIFF (MH, MR, MMR, JBIG2) Grayscale – Color: JPEG | |
| File formats | | Single page: TIFF, JPEG, PDF, High compression PDF, PDF/A Multi page: TIFF, PDF, High compression PDF, PDF/A | |
| Scan modes | | E-mail, Folder, USB, SD Card, URL, FTP | |
| FACSIMILE (STANDARD) | | | |
| Circuit | | PSTN, PBX | |
| Compatibility | | ITU-T (CCITT) G3 | |
| Transmission speed | | 2 seconds | |
| Modem speed: maximum | | 33.6 Kbps | |
| Resolution: standard | | 8 x 3.85 line/mm, 200 x 100 dpi, 8 x 7.7 line/mm, 200 x 200 dpi | |
| Compression method | | MH, MR, MMR, JBIG | |
| Scanning speed | | 40 spm (simplex) / 80 spm (duplex) | |
| PAPER HANDLING | | | |
| Recommended paper size | | Letter, Legal, HLT, A4, A5, B5 | |
| Paper input: standard | 250 sheets | 550 sheets | 550 sheets |
| Paper input: bypass | 100 sheets | 100 sheets | 100 sheets |
| Paper input: maximum | 2,000 sheets | 2,300 sheets | 2,300 sheets |
| Paper output: standard | 100 sheets | 100 sheets | 250 sheets |
| Paper weight | | Trays: 60 – 163 g/m ² Bypass: 60 – 220 g/m ² Duplex: 60 – 163 g/m ² | |
| Paper types | | Plain, Recycled, Special, Color, Letterhead, Cardstock, Preprinted, Bond, Coated, Envelope, Label, OHP | |

LANIER IM C300F/IM C400F/IM C400SRF

MAIN SPECIFICATIONS

| | IM C300F | IM C400F | IM C400SRF |
|----------------------------|-------------------|---|-------------------|
| ECOLOGY | | | |
| Power consumption: maximum | Less than 1,300 W | Less than 1,400 W | Less than 1,400 W |
| Power consumption: sleep | 0.65 W | 0.65 W | 0.65 W |
| TEC* | 0.37 kWh | 0.54 kWh | 0.56 kWh |
| ENERGY STAR® | | Certified | |
| EPEAT® | | Gold Rated* | |
| | | *EPEAT Gold rating is applicable only in the USA. | |

PAPER HANDLING OPTIONS

| | | |
|--|--|---|
| 1 x 550-sheet Paper Feed Unit (PB1170) | | Paper size: Letter, Legal, HLT, A4, A5, B5 Paper weight: 60 – 163 g/m ² |
| 1 x 100-sheet Bin Tray (BN1040) | | Paper size: Letter, Legal, HLT, A4, A5, B5 Paper weight: 60 – 163 g/m ² |

OTHER OPTIONS

Caster Table Type Y, Low Cabinet Type V, Medium Cabinet Type W, Tall Cabinet Type X, IEEE 802.11a/g/n Interface Unit Type M19, NFC Card Reader Type M13, Page Keeper Type M28, PostScript3 Unit Type M41, VM CARD Type M37, ESP XG-PCS-15D Power Filter, ESP S1 Power Filter

CONSUMABLES

| | | | |
|--|---------------|---------------|----------------|
| Toner: black (regular yield) | 17,000 prints | 17,000 prints | 17,000 prints |
| Toner: cyan/magenta/yellow (regular yield) | 6,000 prints | 6,000 prints | 6,000 prints |
| Toner: black (high yield) | N/A | 17,500 prints | 17,500 prints |
| Toner: cyan/magenta/yellow (high yield) | N/A | 8,000 prints | 8,000 prints |
| Staple set | N/A | N/A | 5,000 staples |
| Staple refill | N/A | N/A | 10,000 staples |

Consumable yield measuring method based on A4, 5% coverage

*TEC value is measured based on the ENERGY STAR Ver. 3.0 test method.

Some options may not be available at the time of market release.

Specifications are subject to change without notice.

For maximum performance and yield, we recommend using genuine Lanier parts and supplies.

Some features may require additional options and/or charges.



Ricoh USA, Inc.

300 Eagleview Boulevard
Exton, PA 19341



1-855-5-LANIER



www.lanier.com

LANIER

Ricoh USA, Inc., 300 Eagleview Boulevard, Exton, PA 19341, 1-855-5-LANIER

©2020 Ricoh USA, Inc. All rights reserved. Lanier™ and the Lanier logo are trademarks of Ricoh USA, Inc. Ricoh® and the Ricoh Logo are registered trademarks of Ricoh Company Ltd. All other trademarks are the property of their respective owners. Lanier products and services are offered by Ricoh USA, Inc. and its affiliates. The content of this document, and the appearance, features and specifications of Lanier products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Lanier products and services are as set forth in the express warranty statements accompanying them.