

Colour Production Printer

# RICOH Pro C5300s/C5310s

**RICOH**  
imagine. change.



Pro C5300s

65 ppm  
monochrome  
and full-colour

Pro C5310s

80 ppm  
monochrome  
and full-colour

JOURNEY WITH TEXTURE



JACKSON GROUP  
UP WITH THE LATEST RULES  
REGULATIONS IN HUMAN RESOURCES.

THE JACKSON GROUP  
HUMAN RESOURCES & CONSULTING

HOW TO  
B2B HOME

WE ARE A VALUES-DRIVEN COMPANY.  
OUR MISSION IS TO DELIVER THE BEST EXPERIENCE FOR OUR CLIENTS AND EMPLOYEES.

THE MORI HOTELS + RESORTS  
We build, fix, and manage so you can focus.

WE'RE NO STRANGERS TO LIFE SCIENCES TALENT.  
THE O'CONNOR GROUP HAS HELPED PHARMACEUTICAL, BIOTECH, AND RESEARCH FIRMS ATTRACT AND RETAIN A BROAD RANGE OF TALENT.

OUR PROCESS IS BUTTONED UP AND COMES TO PROFESSIONAL SERVICES.  
FROM LEADING LEGAL FIRMS TO ENGINEERING FIRMS, WE HAVE EXPERIENCE WITH CLIENTS IN A VARIETY OF PROFESSIONAL SERVICES ORGANIZATIONS.

THE MORI HOTELS + RESORTS  
THE COAST IS CLEAR

THE MORI HOTELS + RESORTS  
THE COAST IS CLEAR



cocktail sauce  
\$9  
cheese, sour cream  
OMG \$10  
stuffed mushroom  
stuffed, fried golden  
a zesty Texas  
PIZZA SALAD \$9  
stuffed in our homemade  
homemade croissants

Izzy's Bar & Grill



THE MORI HOTELS + RESORTS  
THE COAST IS CLEAR

THE MORI HOTELS + RESORTS  
THE COAST IS CLEAR

# The quality and reliability you need with the size and affordability you want.

The RICOH Pro C5300s/C5310s, built as a right-sized solution, combines high-quality colour, exceptional media handling, powerful performance, and a range of finishing options. With professional-grade speeds and advanced technologies, they deliver a total package. And it all comes in a compact footprint.

## **Capture and capitalize on more opportunities.**

- High productivity with full-colour output up to 80 ppm
- Exceptional image quality with VCSEL Laser resolutions up to 2400 × 4800 dpi
- Best-in-class media support for specialty stocks, oversized sheets and heavier weights
- Accurate registration and colour consistency for higher-quality jobs
- Automatic duplexing up to 13" × 19.2" and weights to 360 gsm
- Intuitive user controls with a 10" Smart Operation Panel
- Expansive selection of finishing options for greater flexibility
- Choice of Ricoh and EFI Controllers to match workflows
- Integrate with Ricoh software solutions to create efficiencies that drive measurable results — from prepress to job and device management
- ENERGY STAR® certified for lower operating costs and sustainability goals
- User authentication and data encryption protect sensitive information





# The right features. The right size. In the right place.

## Marketing Agencies

Set your firm up for more wins with a compact, high-caliber colour printer that's easy-to-use and requires minimal maintenance.

- Always be ready to deliver professional presentations that show off the genius of your ideas with vibrant colour and pristine image quality.
- Give teams the ability to explore their creativity and fully execute concepts across more media types.
- Produce compelling comps for client approval and provide your print service provider with proofs to ensure your vision is produced as intended.
- Benefit from the convenience of having professional finishing in a streamlined design.

## In-plants

Keep more work in-house and remain a vital resource with an affordable system that enhances your productivity and creates efficiencies.

- Exceed customer expectations with precise registration and the ability to match more colours.
- Offer more applications with support for a wide range of media including specialty stocks, synthetics, envelopes and oversized sheet options.
- Create professionally-finished booklets, course guides, marketing materials and more with tab inserts and thick covers.
- Meet compliance requirements with robust security and support sustainability goals with a system that is Energy Star and EPEAT Gold certified.



## Commercial Printers

Offload short-run jobs from high-volume systems to balance workload and increase your margins.

- Run client proofs for specialty jobs that require colour matching approval.
- Gain a high-quality, dependable system to handle rush jobs and workload spikes.
- Print on-demand work such as flyers, inserts and postcards on coated media and heavy weight stocks.


## Franchise/Pay-for-print:

Grow your business with a dedicated colour printer that easily manages an expansive range of media.

- Reliable performance and intuitive controls make it easy for operators of all levels to run the system.
- Command premium prices with vibrant colour, precise registration and high-quality image reproduction.
- Offer customers more unique options with specialty stocks and produce high-value applications on demand with oversized media options.

The success of your business depends on technology that can help you achieve your productivity and profit goals. And you require high-quality output that meets the demands of your most important clients. The RICOH Pro C5300s/C5310s delivers on both — brilliantly.

Configure a true end-to-end solution with **robust finishing options and software** to match your workflow.



## Powerful controllers to manage your workflow.

The RICOH Pro C5300s/C5310s comes standard with Ricoh's versatile GW controller and offers two unique EFI options. The embedded Fiery E-27B provides robust job and colour management, while the server based Fiery E-47B provides even more power for a higher-level of performance and control over job processing — from make-ready to delivery.

- 1 Produce full-colour booklets in-house and in-line:** Choose the 3,500-Sheet SR5120 Booklet Finisher to create saddle-stitch booklets up to 30 sheets/120 pages. For fully automated wire-bound booklets choose the GBC StreamWire.
- 2 Keep jobs running continually:** With the High Capacity Stacker SK5040 you can stack up to 5,000 sheets and easily move it with a Roll-Away Cart.
- 3 Eliminate offline manual insertion:** Add a one-tray or two-tray Cover Interposer to easily feed preprinted inserts and covers into your workflow.
- 4 Avoid job redos:** Reduce toner adhesion on stacked, coated paper when you use the optional Buffer Pass Unit to cool media before sending it to the finishing unit.




- 5 Keep jobs flowing through production:** Install the optional Decurl Unit to minimize paper curling and improve stacking.
- 6 Streamline information capture:** Copy and scan jobs up to 240 images per minute using the standard 220-Sheet Document Feeder, which scans duplex colour in a single pass.
- 7 Be known for superb reproduction quality:** Deliver brilliant colour and smooth, subtle gradations with Vertical Cavity Surface Emitting Laser (VCSEL) technology and PxP-EQ toner technology.
- 8 Refill paper without downtime:** Rely on the Active Tray Indicators to tell you which tray is in use so you can fill other trays while the system is running.
- 9 Know immediately when a system needs attention:** View the Status Light Pole from anywhere in the room.
- 10 Speed through job instructions:** Complete tasks quickly and easily using the 10" Smart Operation Panel with tablet-like features.
- 11 Accurate front-to-back registration:** The Bridge Unit BU5030, which is required with the Vacuum Feed LCIT, ensures precise registration in this compact footprint.
- 12 Produce long runs:** The Vacuum Feed LCIT RT5120 adds 4,400-sheets of media with support for coated and heavy stocks up to 360 gsm, in sizes up to 13" x 19.2".



# Innovative technology. Superior colour. **High productivity.**

---



## **An outstanding design that delivers on every level.**

**Developed to be a superior product in a compact footprint, without compromise.**

- Smart features include the 10" Smart Operation Panel that guides an intuitive user experience.
- Trained Customer Replaceable Units (TCRUs) allow you to execute routine maintenance on your schedule, ensuring the system is up and running when you need it most.
- Active tray indicator lights allow media to be loaded on-the-fly, increasing efficiency for longer runs and fewer interruptions.



## **The power to help your business do more.**

**Gain a competitive edge with features that help reduce labor intensive set-up, minimize wasted output and achieve repeatable, high-quality results.**

- Six media pick points offer the flexibility to boost production speeds with minimal intervention — delivering exceptional output on time and on budget.
- Built-in sensors drive automation for precise front-to-back registration, producing high-quality results when duplexing business cards, direct mail, books, brochures and invitations.
- End-to-end solutions for Web-to-Print and variable data, allow you to take on more jobs and drive higher response rates for your customers.



## **True-to-life colour that meets customer needs.**

**Benefit from the same imaging technologies that drive Ricoh's larger volume award-winning systems and deliver incredible details that make an impact.**

- Ricoh's Vertical Cavity Surface Emitting Laser (VCSEL) technology delivers the industry's highest pixel density (4800 dpi) for the most vivid images and crisp text with shape lines.
- Parallel calibration delivers high-image quality and consistent colour page after page so you can confidently match brand colours and satisfy the most discerning customer.
- Proprietary PxP-EQ Toner enhances the smooth appearance of images on textured stocks and gloss media.





## Exceptional paper-handling and professional finishing.

Produce high-value applications and bring previously outsourced jobs in-house.

- End-to-end finishing options include traditional stapling and hole-punching to GBC punching, inline multi-folding, and cover interposers that permit pre-printed inserts to be inserted into the workflow.
- Raise the bar with the new SR5120 Booklet Finisher for saddle-stitch books, up to 120 pages, with heavy weight covers up to 350 gsm.
- For workflows that rely on coated media, the Vacuum Feed LCIT provides enhanced support with two multi-tray feeds for longer runs.



## More media. More applications. More profit.

Expand your customer base with eye-catching output, no matter what industry you serve.

- Streamline job setup and achieve optimal output with 1,000 preset or custom profiles in an intuitive Paper Library.
- Produce impressive posters, printed tab inserts, book wraps, panel mailers, full-size tri-fold brochures and more.
- Create a range of applications with extensive media choices from light-weight gloss sheets to the most interesting synthetic and textured stocks.



## A total solution with software and services.

Tap into Ricoh's expertise to realize the full potential of your RICOH Pro C5300s/C5310s. Our experienced team will assess your needs and recommend the solutions to meet your goals.

- Rely on a partnership that gives you 24/7 support and one of largest service organizations dedicated 100% to production.
- Lower reprint costs and gain the highest colour fidelity with Colour Management Services.
- Increase the speed and accuracy of pre-press with TotalFlow® Prep and automate your production printing with TotalFlow® BatchBuilder, a solution that batches jobs based on attributes.

# RICOH Pro C5300s/C5310s

System specifications

## Specifications

|   |   |
|---|---|
| <b>Standard Modes</b>                         | Copy/Print/Scan   |
| <b>Print/Copy Process</b>                     | 4 drum dry electrostatic transfer system with internal transfer belt  |
| <b>Fusing</b>                                 | Oil-less belt fusing method   |
| <b>Toner</b>                                  | Colour P&P-EQ Toner   |
| <b>Paper Registration</b>                     | Sensor and Optional Mechanical Registration   |
| <b>Document Feeder</b>                        | 220-Sheet ADF with single-pass colour duplex scanning at up to 240 ipm  |
| <b>Fax</b>                                    | Optional  |
| <b>Operation Panel</b>                        | Full Colour 10.1" Smart Operation Panel   |
| <b>Output Speed (Letter)</b>                  | Pro C5310s: 80 ppm (52 - 256 gsm)<br>56 ppm (256.1 - 360 gsm)<br>Pro C5300s: 65 ppm (52 - 256 gsm)<br>50 ppm (256.1 - 360 gsm)  |
| <b>First Copy Output Time</b>                 | Pro C5310s: (FC) Less than 9.6 seconds (B&W) Less than 8.1 sec<br>Pro C5300s: (FC) Less than 11 sec (B&W) Less than 9.2 sec   |
| <b>Max Monthly Volume</b>                     | 150K  |
| <b>Duty Cycle</b>                             | 450K  |
| <b>Resolution</b>                             | VCSEL: 2400 x 4800 dpi<br>Print: 1200 x 4800 dpi<br>Copy: 600dpi<br>Scan: 600dpi  |
| <b>Paper Capacity</b>                         | Tray 1: 2,500 sheets (1,250 x 2)<br>Trays 2 - 3: 550 x 2<br>Bypass Tray: 250 sheets   |
| <b>Total Standard Paper Capacity</b>          | 3,850 sheets  |
| <b>Total Max Paper Capacity</b>               | 8,550 sheets  |
| <b>Paper Size</b>                             | Tray 1: 8.5" x 11"<br>Trays 2 - 3: 3.94" x 5.5" to 13" x 19.2"<br>Bypass: 3.94" x 5.5" to 13" x 49.6",<br>Envelopes   |
| <b>Paper Weight</b>                           | Trays 1 - 3: 14 lb. Bond - 110 lb. Cover (52 - 300 gsm)<br>Bypass Tray: 14 lb. Bond - 130 lb. Cover (52 - 360 gsm)<br>Auto Duplex: 14 lb. Bond - 130 lb. Cover (52 - 360 gsm) |
| <b>Maximum Printable Area on 13 x 19.2"</b>   | 12.7" x 18.9"   |
| <b>Warm-up Time</b>                           | Less than 120 seconds   |
| <b>Typical Electricity Consumption (TEC)*</b> | Pro C5300s: 5.813kWh/wk<br>Pro C5310s: 7.273kWh/wk  |
| <b>Max. Power Consumption ENERGY STAR 3.0</b> | 3,840 W or less   |
| <b>EPEAT</b>                                  | Certified<br>Gold Rated   |
| <b>Power Requirements</b>                     | 208 - 240V, 16A, 60 Hz (dedicated)  |
| <b>Dimensions (W x D x H)</b>                 | 31.4" x 34.6" x 64.9"<br>(incl. ADF and Status Light Pole)  |
| <b>Weight</b>                                 | Less than 576.4 lbs.  |

\*Typical Electricity Consumption by ENERGY STAR program.

## Printer Controller

|                                    |  |
|------------------------------------|--|
| <b>EFI Colour Controller E-47B</b> |  |
| <b>Fiery System Version</b>        | Fiery FS400 Pro  |
| <b>Configuration</b>               | Server Type  |
| <b>Memory</b>                      | 8GB RAM  |
| <b>CPU</b>                         | Intel Core i5-6500 processor<br>(3.2GHz up to 3.6GHz with Turbo) |
| <b>HDD</b>                         | 1TB SATA   |
| <b>Operating System</b>            | Windows 10 IoT Enterprise 2019 LTSC                              |
| <b>EFI Colour Controller E-27B</b> |  |
| <b>Fiery System Version</b>        | Fiery FS400 Pro  |
| <b>Configuration</b>               | Embedded Type  |
| <b>Memory</b>                      | 4GB  |
| <b>CPU</b>                         | Intel Pentium processor G4400 3.3GHz                             |
| <b>HDD</b>                         | 500GB  |
| <b>Operating System</b>            | Linux  |

## Accessories

|  |  |
|--|--|
| <b>A4/LT Large Capacity Input Tray (LCIT RT4060)</b>                           |  |
| <b>Paper Capacity</b>  | 4,400 sheets                               |
| <b>Paper Size</b>  | 8.5" x 11"                                 |
| <b>Paper Weight</b>  | 14 lb. Bond - 80 lb. Cover (52 - 216 gsm)  |
| <b>Dimensions (W x D x H)</b>  | 13.8" x 21.3" x 24.6"                      |
| <b>Weight</b>  | 44 lbs.                                    |
| <b>A3/DLT Large Capacity Input Tray (LCIT RT5140)</b>                          |  |
| <b>Paper Capacity</b>  | 2,200 sheets                               |
| <b>Paper Size</b>  | 3.94 x 5.5" - 13" x 19.2"                  |
| <b>Paper Weight</b>  | 14 lb. Bond - 110 lb. Cover (52 - 300 gsm) |
| <b>Dimensions (W x D x H)</b>  | 34.2" x 28.7" x 25.9"                      |
| <b>Weight</b>  | 180 lbs.                                   |
| <b>Banner Sheet Guide Tray for A3/11"x17" LCIT Type S6</b>                     |  |
| <b>Paper Capacity</b>  | 250 sheets                                 |
| <b>Paper Size</b>  | up to 13" x 27.5"                          |
| <b>Paper Weight</b>  | 14 lb. Bond - 110 lb. Cover (52 - 300 gsm) |
| <b>Vacuum Feed Large Capacity Input Tray (LCIT RT5120)</b>                     |  |
| <b>Paper Capacity</b>  | 4,400 sheets (2,200 sheets x 2 Trays)      |
| <b>Paper Size</b>  | 3.94" x 5.5" - 13" x 19.2"                 |
| <b>Paper Weight</b>  | 14 lb. Bond - 130 lb. Cover (52 - 360 gsm) |
| <b>Dimensions (W x D x H)</b>  | 41.5" x 28.7" x 39.4"                      |
| <b>Weight</b>  | 507 lbs.                                   |
| <b>Carbonless Paper supported with optional Carbonless Paper Unit Type S13</b> |  |
| <b>Bridge Unit BU5030 (Required for the LCIT RT5120)</b>                       |  |
| <b>Mechanical Registration included</b>  |  |
| <b>Dimensions (W x D x H)</b>  | 8.85" x 28.2" x 39.4"                      |
| <b>Weight</b>  | 90 lbs.                                    |
| <b>Vacuum Feed Oversize Sheet Tray Type S9</b>                                 |  |
| <b>Paper Capacity</b>  | 730 sheets                                 |
| <b>Paper Size</b>  | 8.27" x 16.54" - 13" x 27.5"               |
| <b>Paper Weight</b>  | 14 lb. Bond - 130 lb. Cover (52 - 360 gsm) |
| <b>Width of LCIT RT5120 will extend to 50.8"</b>                               |  |

|                                       |   |
|---------------------------------------|---|
| <b>Multi Bypass Tray (BY5020)</b>     |   |
| <b>Paper Capacity</b>                 | 500 sheets  |
| <b>Paper Size</b>                     | 3.94" x 5.5" - 13" x 19.2"  |
| <b>Maximum Paper size</b>             | extends up to 13" x 27.5" by adding the optional<br>Multi Bypass Oversize Sheet Tray Type S9  |
| <b>Paper Weight</b>                   | 14 lb. Bond - 80 lb. Cover (52 - 216 gsm)   |
| <b>Cover Interposer (CI5050)</b>      |   |
| <b>Paper Capacity</b>                 | 200 sheets (200 sheets x 1 Tray)  |
| <b>Paper Size</b>                     | 5.5" x 8.5" - 11" x 17"   |
| <b>Paper Weight</b>                   | 17 lb. Bond - 80 lb. Cover (64 - 216 gsm)   |
| <b>Dimensions (W x D x H)</b>         | 19.7" x 23.6" x 23.6"   |
| <b>Weight</b>                         | 26 lbs.   |
| <b>Cover Interposer (CI5040)</b>      |   |
| <b>Paper Capacity</b>                 | 400 sheets (200 sheets x 2 Trays)   |
| <b>Paper Size</b>                     | 5.5" x 8.5" - 13" x 19.2"   |
| <b>Paper Weight</b>                   | 14 lb. Bond - 130 lb. Cover (52 - 350 gsm)  |
| <b>Air Assist</b>                     | Supported   |
| <b>Double Feed Detection</b>          | Supported   |
| <b>Dimensions (W x D x H)</b>         | 13" x 28.7" x 50.8"   |
| <b>Weight</b>                         | 110 lbs.  |
| <b>Multi Folding Unit FD5020</b>      |   |
| <b>Folding Type</b>                   | Single Sheet Mode: Z-Fold, Half-Fold/Print inside, Half-Fold/Print outside, Letter Fold-in/Print inside, Letter Fold-in/Print outside, Letter Fold-out, Double Parallel/Print inside, Double Parallel/Print outside, Gate-Fold/Print inside, Gate-Fold/Print outside<br>Multiple Sheets Mode: Half-Fold/Print inside, Half-Fold/Print outside, Letter Fold-in/Print inside, Letter Fold-in/Print outside, Letter Fold-out |
| <b>Paper Size</b>                     | Single Sheet Mode: Z folding: 8.5" x 11" - 12" x 18"; Half folding: 8.5" x 11" - 13" x 19.2"; Letter folding: 8.5" x 11" - 12" x 18"; Double Parallel folding: 8.5" x 11" - 12" x 18"; Gate folding: 8.5" x 11" - 12" x 18"<br>Multiple Sheets Mode: Half folding: 8.5" x 11" - 13" x 19.2"; Letter Fold-in: 8.5" x 11" - 12" x 18"; Letter Fold-out: 8.5" x 11" - 8.5" x 14"   |
| <b>Paper Weight</b>                   | Single Sheet Mode: 17 lb. Bond - 28 lb. Bond (64 - 105 gsm)<br>Multiple Sheets Mode: 17 lb. Bond - 21 lb. Bond (64 - 80 gsm)  |
| <b>Dimensions (W x D x H)</b>         | 18.5" x 28.7" x 39.4"   |
| <b>Weight</b>                         | 203 lbs.  |
| <b>High Capacity Stacker (SK5040)</b> |   |
| <b>Paper Capacity</b>                 | 5,000 sheets  |
| <b>Proof tray</b>                     | Additional 250 sheets   |
| <b>Paper Weight</b>                   | 14 lb. Bond - 130 lb. Cover (52 - 360 gsm)  |
| <b>Rollaway Cart</b>                  | Standard and Optional additional carts available  |
| <b>Dimensions (W x D x H)</b>         | 35.4" x 28.7" x 39.8"   |
| <b>Weight</b>                         | Stacker: 264 lbs.; Rollaway cart: 33 lbs.   |



#### Copy Tray Type M42

|                        |  |
|------------------------|--|
| Paper Capacity         | 500 sheets                                 |
| Paper Size             | 3.94" x 5.5" – 13" x 19.2"                 |
| Paper Weight           | 14 lb. Bond – 130 lb. Cover (52 – 360 gsm) |
| Dimensions (W x D x H) | 13.8" x 19.7" x 6.7"                       |
| Weight                 | 4.85 lbs.                                  |

#### 3,000-Sheet Finisher with 65-Sheet Stapler (SR5090)

|                        |  |
|------------------------|--|
| Shift Tray             |  |
| Paper Capacity         | 3,000 sheets                                       |
| Paper Weight           | 14 lb. Bond – 130 lb. Cover (52 – 360 gsm)         |
| Proof Tray             |  |
| Paper Capacity         | 250 sheets   |
| Paper Weight           | 14 lb. Bond – 80 lb. Cover (52 – 216 gsm)          |
| Paper Size             | 3.94" x 5.5" – 13" x 19.2"                         |
| Output Jogger          | Optional   |
| Cooling Fan            | Optional   |
| Punch 2/3 hole         | Optional   |
| Staple                 |  |
| Paper Size             | 8.5" x 11", 8.5" x 14", 11" x 17" – 2 to 65 sheets |
| Staple Paper Weight    | Up to 105 gsm                                      |
| Staple Position        | Top, Bottom, 2 Staples, Top Slant                  |
| Dimensions (W x D x H) | 25.9" x 28.7" x 38.6"                              |
| Weight                 | 83.7 lbs.  |

#### 2,000-Sheet Booklet Finisher with 65-Sheet Stapler (SR5100)

|                 |   |
|-----------------|---|
| Shift Tray      |   |
| Paper Capacity  | 2,000 sheets  |
| Paper Weight    | 14 lb. Bond – 130 lb. Cover (52 – 360 gsm)              |
| Proof Tray      |   |
| Paper Capacity  | 250 sheets  |
| Paper Weight    | 14 lb. Bond – 80 lb. Cover (52 – 216 gsm)               |
| Output Jogger   | Optional  |
| Cooling Fan     | Optional  |
| Punch 2/3 hole  | Optional  |
| Staple          |   |
| Paper           | Size 8.5" x 11", 8.5" x 14", 11" x 17" – 2 to 65 sheets |
| Paper Position  | Weight Up to 105 gsm                                    |
| Staple Position | Top, Bottom, 2 Staples, Top Slant                       |

#### Saddle Stitch Staple

|                        |                             |
|------------------------|-----------------------------|
| Paper Size             | 8.5" x 11" – 13" x 18"      |
| Paper Weight           | 64-80 gsm – up to 20 sheets |
| Position               | 2 at center                 |
| Dimensions (W x D x H) | 25.9" x 28.7" x 38.6"       |
| Weight                 | 128.7 lbs.                  |

#### 4,500-Sheet Finisher with 100-Sheet Stapler (SR5110)

|                        |  |
|------------------------|--|
| Paper Capacity         | 4,500 sheets                               |
| Lower Shift Tray       | 3,500 sheets                               |
| Upper Shift Tray       | 1,000 sheets                               |
| Paper Weight           | 14 lb. Bond – 130 lb. Cover (52 – 360 gsm) |
| Punch 2/3 hole         | Optional                                   |
| Dimensions (W x D x H) | 39.2" x 28.7" x 55.7"                      |
| Weight                 | 298 lbs.                                   |

#### 3,500-Sheet Booklet Finisher with 100-Sheet Stapler (SR5120)

|                        |  |
|------------------------|--|
| Paper Capacity         | 2,500 sheets                               |
| Lower Shift Tray       | 1,000 sheets                               |
| Upper Shift Tray       | 1,000 sheets                               |
| Paper Weight           | 14 lb. Bond – 130 lb. Cover (52 – 360 gsm) |
| Punch 2/3 hole         | Optional                                   |
| Saddle Stitch Staple   | 14 lb. Bond – 130 lb. Cover (52 – 350 gsm) |
| Paper Size             | 7.2" x 10.2" – 13" x 19.2"                 |
| Paper Weight           | 52 – 80 gsm up to 30 sheets / 120 pages    |
| Dimensions (W x D x H) | 39.2" x 28.7" x 55.7"                      |
| Weight                 | 353 lbs.                                   |

#### Booklet Trimmer (TR5050)

|                        |   |
|------------------------|---|
| Trimming Type          | One Side Edge   |
| Trimming Capacity      | up to 30 stapled and folded sheets / 120 pages (80 gsm) |
| Paper Size             | 7.2" x 10.2" – 13" x 19.2"                              |
| Stack Capacity         | Up to 60 sets   |
| Limitless Stack        | Supported   |
| Dimensions (W x D x H) | 43.9" x 23.3" x 21.9"                                   |
| Weight                 | 166 lbs.  |

#### GBC StreamPunch Ultra

|                        |   |
|------------------------|---|
| Paper Sizes            | 5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", 12" x 18" |
| Paper Weight           | 20 lb. Bond – 110 lb. Cover (75 – 300 gsm)                |
| Tab Punching           | Supported   |
| "Two-Up" Punching      | Supported   |
| Dimensions (W x D x H) | 17.5" x 28.7" x 39.4"                                     |
| Weight                 | 220 lbs.  |

#### GBC StreamWire (GBC StreamPunch Ultra is required)

|                        |  |
|------------------------|--|
| Paper Sizes            | 8.5" x 11" (LEF)                           |
| Paper Weight           | 20 lb. Bond – 110 lb. Cover (75 – 300 gsm) |
| Number of Loops        | 8.5" x 11" (LEF) – 32 loops                |
| StreamWire Supply      | Black, White, or Silver                    |
| Tab Stack              | Up to 30, 50, 60, 70, or 80 Sheets         |
| Dimensions (W x D x H) | Supported                                  |
| Weight                 | 34" x 38" x 34"                            |
|                        | 500 lbs.                                   |

#### Plockmatic Square Back Trimmer

|                        |   |
|------------------------|---|
| Trimming Type          | One Side Edge   |
| Three side Trimming    | Manual feeding via Operator assisted process            |
| Folding Type           | Square Back Fold  |
| Trimming Capacity      | up to 30 stapled and folded sheets / 120 pages (80 gsm) |
| Paper Size             | 7.2" x 10.2" – 13" x 19.2"                              |
| Dimensions (W x D x H) | 69.3" x 26" x 41.9"                                     |
| Weight                 | 392 lbs.  |

#### Plockmatic PBM350e Booklet Maker

|                        |  |
|------------------------|--|
| Paper Size             | 8.5" x 11" – 12" x 18"   |
| Paper Weight           | 17 lb. Bond – 110 lb. Cover (64 – 300 gsm)                         |
| Set Size               | 2 – 35 sheets – 80 gsm   |
|                        | 2 – 50 sheets – 80 gsm (PBM500 upgrade kit needed)                 |
| Dimensions (W x D x H) | 55.9" x 35.4" x 27.6"  |
| Weight                 | 297 lbs.   |
| Optional               | Trim Module, Book Fold Module, Cover Feeder, Rotate Crease Trimmer |

#### Additional Accessories

Decurl Unit DU5080, Buffer Pass Unit Type S9, Bridge Unit BU5020, Media Identification Unit, PostScript® Unit Type M42, IPDS Unit Type M42, VM Card Type P18, OCR Unit Type M13

#### Consumables

|                          |                     |
|--------------------------|---------------------|
| CMY Toner Yield          | 26K prints/bottle*  |
| K Toner Yield            | 31K prints/bottle*  |
| Waste Toner Bottle Yield | 110K prints/bottle* |

\*Based on 8.75% coverage (Letter)

TCRU Program Supported

#### Workflow Solutions Supported

Ricoh Streamline NX, Ricoh Global Scan NX, Ricoh Integrated Cloud Environment, Ricoh Smart Integration, RICOH ProcessDirector®, RICOH TotalFlow Prep, RICOH TotalFlow Production Manager, RICOH TotalFlow BatchBuilder, RICOH @Remote, EFI® DigitalStoreFront®, CGS/ORIS Lynx & Evaluate, EFI Colour Profiler Suite, EFI Fiery® Graphic Arts Pro, EFI Fiery ColourRight, EFI Fiery Automation, DirectSmile®, EFI Fiery Central, Objectif Lune

Specifications subject to change without notice. Contact Ricoh for a list of certified media.

**RICOH**  
imagine. change.

[www.ricoh.ca](http://www.ricoh.ca)

Ricoh Canada Inc., 100-5560 Explorer Drive, Mississauga, ON L4W 5M3, 1-888-742-6417  
©2020 Ricoh Canada Inc. All rights reserved. Ricoh and the Ricoh logo are registered trademarks of Ricoh Company, Ltd. All other trademarks are the property of their respective owners. The content of this document, and the appearance, features and specifications of Ricoh products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Ricoh products and services are as set forth in the express warranty statements accompanying them.